

DIN EN ISO 12569:2013-03 (E)

Thermal performance of buildings and materials - Determination of specific airflow rate in buildings - Tracer gas dilution method (ISO 12569:2012)

Contents	Page
Foreword	3
Introduction	4
1 Scope	5
2 Terms and definitions	5
3 Measurement method and its selection	6
3.1 General.....	6
3.2 Concentration decay method.....	8
3.3 Continuous dose method.....	11
3.4 Constant concentration method.....	13
3.5 Type of tracer gas.....	14
3.6 Measurement apparatus.....	15
4 Procedure	17
4.1 Building preparations.....	17
4.2 Ancillary measurements.....	17
4.3 Concentration decay method.....	17
4.4 Continuous dose methods.....	24
4.5 Constant concentration method.....	29
5 Accuracy	31
5.1 Tracer gas dose procedure and room concentration distribution.....	32
5.2 Tracer gas sampling and storage method.....	32
5.3 Tracer gas concentration measuring instruments.....	32
5.4 Changes in outside wind and outside air temperature and schedule of air conditioning system.....	33
6 Test report	33
6.1 General.....	33
6.2 All details necessary to identify the simulation tested.....	33
6.3 Details of heating and ventilation systems.....	33
6.4 Test conditions and apparatus.....	34
6.5 Collected data and results.....	34
6.6 Date of the test.....	34
Annex A (normative) Confidence intervals	35
Annex B (normative) Method to estimate ventilation rate Q_V and effective mixed zone volume V_{emz} simultaneously [3,4]	39
Annex C (informative) Considerations when measuring the ventilation rate of large spaces	43
Annex D (informative) Effects of internal and external temperature difference, temperature change, and outside air concentration change during the measurement period	44
Annex E (informative) Estimation error minimizing method in 2-point and multi-point decay method	48
Annex F (informative) Propagation of error analysis	53
Bibliography	55