

DIN 18177:2012-11 (E)

Wet-felt factory-produced mineral panels - Characteristics and test methods

Contents		Page
Foreword		3
Introduction		4
1	Scope	5
2	Normative references	5
3	Terms, definitions, symbols and abbreviated terms	6
4	Requirements	10
4.1	General requirements	10
4.2	Special requirements	13
5	Test methods	16
5.1	Determination of width	16
5.2	Determination of length	16
5.3	Determination of thickness	17
5.4	Determination of density	18
5.5	Determination of angularity	18
5.6	Determination of edge dimensions	19
5.7	Determination of applied amount of coating	19
5.8	Determination of loss on ignition	20
5.9	Determination of flexural strength	20
5.10	Reaction to fire	20
5.11	Dimensional stability under specified conditions of temperature and humidity	21
5.12	Light reflectance	21
5.13	Determination of release of volatile organic compounds (VOC)	21
5.14	Determination of release of formaldehyde and other carbonyl compounds	22
5.15	Determination of air permeability	23
5.16	Determination of compressive strength	23
5.17	Determination of point load	23
5.18	Determination of thermal resistance and thermal conductivity	23
5.19	Determination of deflection	24
6	Evaluation of conformity	25
6.1	General	25
6.2	Type testing	25
6.3	Factory production control	26
7	Designation of mineral boards	27
Annex A (normative) Mounting and fixing for testing in accordance with DIN EN 13823 (SBI test)		28
A.1	General requirements	28