

ISO 12569:2012-12 (E)

Thermal performance of buildings and materials - Determination of specific airflow rate in buildings - Tracer gas dilution method

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Terms and definitions	1
3	Measurement method and its selection	2
3.1	General	2
3.2	Concentration decay method	4
3.3	Continuous dose method	7
3.4	Constant concentration method	9
3.5	Type of tracer gas	10
3.6	Measurement apparatus	11
4	Procedure	13
4.1	Building preparations	13
4.2	Ancillary measurements	13
4.3	Concentration decay method	13
4.4	Continuous dose methods	20
4.5	Constant concentration method	25
5	Accuracy	27
5.1	Tracer gas dose procedure and room concentration distribution	28
5.2	Tracer gas sampling and storage method	28
5.3	Tracer gas concentration measuring instruments	28
5.4	Changes in outside wind and outside air temperature and schedule of air conditioning system	29
6	Test report	29
6.1	General	29
6.2	All details necessary to identify the simulation tested	29
6.3	Details of heating and ventilation systems	29
6.4	Test conditions and apparatus	30
6.5	Collected data and results	30
6.6	Date of the test	30
Annex A (normative)	Confidence intervals	31
Annex B (normative)	Method to estimate ventilation rate QV and effective mixed zone volume V_{emz} simultaneously [3,4]	34
Annex C (informative)	Considerations when measuring the ventilation rate of large spaces	39
Annex D (informative)	Effects of internal and external temperature difference, temperature change, and outside air concentration change during the measurement period	40
Annex E (informative)	Estimation error minimizing method in 2-point and multi-point decay method	44

Annex F (informative) Propagation of error analysis	49
Bibliography	51