

ISO 13788:2012-12 (E)

Hygrothermal performance of building components and building elements - Internal surface temperature to avoid critical surface humidity and interstitial condensation - Calculation methods

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions, symbols and units	1
3.1	Terms and definitions	1
3.2	Symbols and units	3
3.3	Subscripts	4
4	Input data for the calculations	4
4.1	Material and product properties	4
4.2	External boundary conditions	4
4.3	Internal boundary conditions	6
4.4	Surface resistances	6
5	Calculation of surface temperature to avoid critical surface humidity	7
5.1	General	7
5.2	Determining parameters	7
5.3	Design for avoidance of mould growth, corrosion or other moisture damage	7
5.4	Design for the limitation of surface condensation on low thermal inertia elements	8
6	Calculation of interstitial condensation	9
6.1	General	9
6.2	Principle	9
6.3	Limitation of sources of error	10
6.4	Calculation	10
6.5	Criteria used to assess building components	16
7	Calculation of drying of building components	16
7.1	General	16
7.2	Principle	17
7.3	Specification of the method	17
7.4	Criteria used to assess drying potential of building components	17
Annex A (informative)	Internal boundary conditions	18
Annex B (informative)	Examples of calculation of the temperature factor at the internal surface to avoid critical surface humidity	20
Annex C (informative)	Examples of calculation of interstitial condensation	24
Annex D (informative)	Example of the calculation of the drying of a wetted layer	34
Annex E (informative)	Relationships governing moisture transfer and water vapour pressure	37
Bibliography		40