ISO 13788:2012-12 (E)

Hygrothermal performance of building components and buildi ng elements - Internal surface temperature to avoid critical surface humidity and interstitial condensation - Calculation methods

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions,symbolsandunits 1
3.1 Terms and definitions 1
3.2 Symbols and units 3
3.3 Subscripts 4

4 Input data for the calculations 4
4.1 Material and product properties 4
4.2 External boundary conditions 4
4.3 Internal boundary conditions 6
4.4 Surface resistances 6

5 Calculation of surface temperature to avoid critical surface humidity 7
5.1 General 7
5.2 Determining parameters 7
5.3 Design for avoidance of mould growth, corrosion or other moisture damage 7
5.4 Design for the limitation of surface condensation on low thermal inertia elements 8

6 Calculation of interstitial condensation 9
6.1 General 9
6.2 Principle 9
6.3 Limitation of sources of error 10
6.4 Calculation 10
6.5 Criteria used to assess building components 16

7 Calculation of drying of building components 16
7.1 General 16
7.2 Principle 17
7.3 Specification of the method 17
7.4 Criteria used to assess drying potential of building components 17

Annex A (informative) Internal boundary conditions 18

Annex B (informative) Examples of calculation of the temperature factor at the internal surface to avoid critical surface humidity 20

Annex C (informative) Examples of calculation of interstitial condensation 24

Annex D (informative) Example of the calculation of the drying of a wetted layer 34

Annex E (informative) Relationships governing moisture transfer and water vapour pressure 37

Bibliography 40