DIN EN 14314:2013-04 (E)

Thermal insulation products for building equipment and indust rial installations - Factory made phenolic foam (PF) products - Specification (includes Amendment A1:2013)

Contents

Page

Foreword 4

1 Scope 6

2 Normative references 6

3 Terms, definitions, symbols, units and abbreviated terms 8

4 Requirements 10

5 Test methods 17

6 Designation code 21

7 Evaluation of conformity 22

8 Marking and labelling 22

Annex A (normative) Factory production control 24

Annex B (normative) Determination of the aged value of thermal conductivity 27

Annex C (normative) Determination of minimum service temperature 31

Annex D (informative) Additional properties 37

Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Directive 39

Bibliography 47

Figures Figure C.1 -- Dimensions of test specimens (mm) 36

Figure ZA.1 -- Example of CE marking information 46

Tables Table 1 -- Dimensional tolerances 12

Table 2 -- Classes for thickness tolerances for boards 12

!Table 3" -- Tolerances for deviation from flatness 13

!Table 4" -- Levels for compressive stress or compressive strength 15

!Table 5" -- Levels of short term water absorption by partial immersion 16

!Table 6" -- Levels for long term water absorption by partial immersion 17

!Table 7" -- Test methods, test specimens and conditions 19

Table A.1 -- Minimum product testing frequencies 24

Table A.2 -- Minimum product testing frequencies for the reaction to fire characteristics 26

Table B.1 -- Increments to be added to accelerated aged values of thermal conductivity to obtain the time averaged value over 25 years 29

Table D.1 -- Test methods, test specimens, conditions and minimum testing frequencies 38

Table ZA.1 -- Relevant clauses 40

Table ZA.2 -- System(s) of attestation of conformity 41

Table ZA.3 -- Assignment of evaluation of conformity tasks for products under system 1 42

Table ZA.4 -- Assignment of evaluation of conformity tasks for products under system 3 or system 3 combined with system 4 for reaction to fire 43