

# DIN 18008-5:2013-07 (E)

## Glass in Building - Design and construction rules - Part 5: Additional requirements for walk-on glazing

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
<b>1</b> <b>Scope</b> .....		4
<b>2</b> <b>Normative references</b> .....		4
<b>3</b> <b>Terms and definitions</b> .....		4
<b>4</b> <b>Construction products</b> .....		4
<b>5</b> <b>Conditions of application</b> .....		5
<b>6</b> <b>Exposure to stress and proof of resistance</b> .....		5
<b>6.1</b> <b>Limit states for static load</b> .....		5
<b>6.2</b> <b>Limit states for impact: stress effects and residual load-bearing capacity</b> .....		5
<b>Annex A (normative) Proof of impact resistance and residual load-bearing capacity by building-</b> <b>component tests</b> .....		6
<b>A.1</b> <b>General</b> .....		6
<b>A.2</b> <b>Test procedure</b> .....		6
<b>A.2.1</b> <b>Proof of impact resistance</b> .....		6
<b>A.2.2</b> <b>Proof of residual load-bearing capacity</b> .....		7
<b>A.2.3</b> <b>Test report</b> .....		7
<b>Annex B (normative) Glass constructions with empirically proven impact resistance and</b> <b>residual load-bearing capacity</b> .....		8
<b>B.1</b> <b>General</b> .....		8
<b>B.2</b> <b>Glazing units linearly supported on all sides</b> .....		8