DIN EN 12602:2013-10 (E)

Prefabricated reinforced components of autoclaved aerated concrete (includes Amendment A1:2013)

Contents

Page

Foreword 10

1 Scope 12

2 Normative references 12

3 Terms, definitions, symbols and abbreviations 14
3.1 Terms and definitions 14
3.2 Symbols 15
3.2.1 General symbols 15
3.2.2 Subscripts 16
3.2.3 Symbols used in this European Standard (including normative annexes, except Annex C) 16
3.3 Abbreviations 22

4 Properties and requirements of materials 22
4.1 Constituent materials of autoclaved aerated concrete 22
4.1.1 General 22
4.1.2 Release of dangerous substances 23
4.2 Autoclaved aerated concrete parameters 23
4.2.1 General 23
4.2.2 Dry density 23
4.2.3 Characteristic strength values 25
4.2.4 Compressive strength 25
4.2.5 Tensile strength and flexural strength 25
4.2.6 Stress-strain diagram 26
4.2.7 Modulus of elasticity 26
4.2.8 Poisson's ratio 26
4.2.9 Coefficient of thermal expansion 27
4.2.10 Drying shrinkage 27
4.2.11 Creep 27
4.2.12 Specific heat 28
4.2.13 Thermal conductivity 28
4.2.14 Water vapour permeability 30
4.2.15 Water tightness 30
4.3 Reinforcement 30
4.3.1 Steel 30
4.3.2 Structural reinforcement 31
4.3.3 Effective diameter of coated bars 32
4.3.4 Non-structural reinforcement 33
4.4 Bond 33
4.5 Thermal prestress 34
4.5.1 General 34
4.5.2 Declared mean initial prestrain 0m,g 34

5 Properties and requirements of components 35
5.1 General 35
5.1.1 Mechanical resistance 35
5.1.2 Acoustic properties 35
5.1.3 Reaction to fire and resistance to fire 35
5.1.4 Design thermal resistance and design thermal conductivity 36

5.2 Technical requirements and declared properties ... 36
5.2.1 Dimensions and tolerances ... 36
5.2.2 Mass of the components ... 37
5.2.3 Dimensional stability ... 37
5.2.4 Load-bearing capacity ... 38
5.2.5 Deflections ... 38
5.2.6 Joint strength ... 38
5.2.7 Minimum requirements ... 39
5.3 Durability ... 41
5.3.1 General ... 41
5.3.2 Environmental conditions ... 41
5.3.3 Corrosion protection of reinforcement ... 42
5.3.4 Freeze and thaw resistance ... 43

6 Evaluation of conformity ... 43
6.1 Introduction ... 43
6.2 Initial type-testing of the component ... 43
6.3 Factory production control ... 44
6.3.1 General ... 44
6.3.2 Process control ... 44
6.3.3 Finished products ... 45
6.4 Initial inspection of the factory and the factory production control ... 45
6.4.1 Information to be supplied ... 45
6.4.2 Inspection ... 45
6.4.3 Reports ... 46
6.5 Surveillance, assessment and acceptance of the factory production control ... 46
6.5.1 Inspection tasks ... 46
6.5.2 Frequency of inspections ... 46
6.5.3 Reports ... 46
6.6 Actions to be taken in the event of non-conformity ... 46

7 Basis for design ... 54
7.1 Design methods ... 54
7.2 Limit states ... 54
7.3 Actions ... 55

8 Marking, labelling and designation ... 55
8.1 Standard designation ... 55
8.2 Production detail information ... 56
8.3 Additional information on accompanying documents ... 56

Annex A (normative) Design by calculation ... 57

A.1 General ... 57
A.2 Ultimate limit states (ULS) General design assumptions ... 57
A.3 Ultimate limit states (ULS): design for bending and combined bending and axial compression ... 59
A.3.1 Design assumptions ... 59
A.3.2 Stress-strain diagram for AAC ... 59
A.3.3 Stress-strain diagram for reinforcing steel ... 60
A.3.4 Minimum reinforcement ... 62
A.4 Shear ... 63
A.4.1 Shear design for components predominantly under transverse load ... 63
A.5 Ultimate limit states induced by structural deformation (buckling) ... 68
A.5.1 General ... 68
A.5.2 Method based on Euler formula ... 69
A.5.3 Modified model column method ... 70
A.6 Punching ... 76
A.6.1 General ... 76
A.6.2 Scope and definitions ... 76
A.6.3 Design method for punching shear ... 78
A.7 Primary torsion/combined primary torsion and shear ... 79

A.8 Concentrated forces 81
A.9 Serviceability limit states (SLS) 82
A.9.1 General 82
A.9.2 Limitation of stresses under serviceability conditions 82
A.9.3 Serviceability limit states of cracking 83
A.9.4 Serviceability limit states of deformation 83
A.10 Detailing of reinforcement 86
A.10.1 General 86
A.10.2 Bond 87
A.10.3 Anchorage 87
A.11 Support length 91

Annex B (normative) Design by testing 93

B.1 General 93
B.2 Safety evaluation 94
B.2.1 General 94
B.2.2 Brittle and ductile failure 94
B.3 Ultimate limit state 94
B.3.1 General 94
B.3.2 Transversely loaded components 95
B.3.3 Longitudinally loaded components 97
B.3.4 Simultaneously transversely and longitudinally loaded wall components 100
B.3.5 Anchorage 101
B.4 Serviceability limit states 103
B.4.1 Crack width control 103
B.4.2 Deformations 103

Annex C (normative) Resistance to fire design of AAC components and structures 104

C.1 General 104
C.1.1 Scope 104
C.1.2 Distinction between principles and application rules 104
C.1.3 Terms and definitions 104
C.1.4 Symbols 106
C.1.5 Units 107
C.2 Basic principles 108
C.2.1 Performance requirements 108
C.2.2 Design values of material properties 108
C.2.3 Assessment methods 108
C.3 Material properties 109
C.3.1 General 109
C.3.2 AAC 110
C.3.3 Steel 112
C.4 Structural fire design methods 113
C.4.1 General 113
C.4.2 Tabulated data 113
C.4.3 Simplified design methods 118
C.4.4 Anchorage 122
C.5 Protective layers 122

Annex CA (normative) Modulus of elasticity and maximum strain of AAC and reinforcing steel at elevated temperature 123

Annex CB (informative) Joints between AAC components satisfying resistance to fire E 126

CB.1 Floor and roof components with dry joints 126

CB.2 Floor and roof components with mortar joints 126

CB.3 Vertical and horizontal wall components with dry joints 127

CB.4 Vertical and horizontal wall components with mortar joints 127

Annex CC (normative) Temperature profiles of AAC wall, floor and roof components and AAC beams 129

CC.1 Basis of temperature profiles 129

CC.2 Temperature profiles for AAC wall, floor and roof components 129

CC.3 Temperature profiles for AAC beams 132

CC.4 Calculation assumptions 141

Annex CD (normative) Resistance to fire tabulated data for walls with mechanical impact 142

Annex D (informative) Recommended values for partial safety factors 144

D.1 General 144
D.2 Ultimate Limit States (ULS) 144
D.3 Serviceability Limit States (SLS) 146

Annex E (informative) Recommendations for the consideration of prestress in the design of prefabricated reinforced AAC components 147

E.1 Calculation of prestrain from test results 147
E.1.1 General 147
E.1.2 Symbols 148
E.1.3 Cross-section values of AAC components 149
E.1.4 Calculation of prestrain 0 from steel measurement 149
E.2 Cross-sectional analysis of a AAC component in SLS if prestress is taken into account 149
E.3 Splitting forces due to prestress 150
E.4 Methods to prevent end cracks due to prestress 151

Annex F (informative) Statistical methods for quality control 152

F.1 Quality control 152

Annex G (normative) !Factory production control of stainless reinforcing steel based on at least three samples - Minimum acceptance criteria for individual values and corresponding mean values" 154

Annex ZA (informative) Provisions for the CE marking of prefabricated reinforced components of autoclaved aerated concrete under the EC Construction Product Directive 155

ZA.1 Clauses of this European Standard addressing the provisions of EC Construction Products Directive 155

ZA.2 Procedures for the attestation of conformity of products 163

ZA.2.1 Systems of attestation of conformity 163

ZA.2.2 EC Certificate and Declaration of conformity 165

ZA.3 CE marking and labelling 166

ZA.3.1 General 166

ZA.3.2 Declaration of geometrical data and material properties 167

ZA.3.3 Declaration of product properties 170

ZA.3.4 Declaration of compliance with given design specification 172

ZA.3.5 !Declaration of compliance with the manufacturers' designed specification" 173

ZA.3.6 Simplified CE-marking label with reference to a manufacturer's catalogue 176

ZA.3.7 !Example on Technical information in the CE-marking" 177

Bibliography 179

Figures Figure 1 -- Determination of dry thermal conductivity 10dry 29

Figure A.1 -- Determination of effective span leff 58

Figure A.2 -- Bi-linear stress-strain diagram for AAC in compression for cross-sectional design 60

Figure A.3 -- Design stress-strain diagram for reinforcing steel 61

Figure A.4 -- Strain diagrams in the ultimate limit state 62

Figure A.5 -- Notation for components subjected to shear 65

Figure A.6 --Structural model and possible load cases for the modified model column method 71

Figure A.7 -- Relation between curvature and strain Two curvatures (great curvature and small curvature) are presented 74

Figure A.8 -- Application of punching provisions in non-standard cases 77

Figure A.9 -- Critical perimeter around loaded areas located away from an unsupported edge 77

Figure A.10 -- Critical perimeter near an opening 78

Figure A.11 -- Critical sections near unsupported edges 78

Figure A.12 -- Idealised box section 81

Figure A.13 -- Definition of the areas to be introduced in Equation (A.39) 82

Figure A.14 -- Moment curvature relationship 86

Figure A.15 -- Effective length of transverse anchorage bars 89

Figure A.16 -- Envelope line for determining the tensile force in the longitudinal reinforcement 90

Figure A.17 -- Support length ao 92

Figure B.1 -- Definition of shear span ls 95

Figure B.2 -- Typical reinforcement layouts in AAC-components 96

Figure B.3 -- Diagram for determination of the column factor k 99

Figure B.4 -- N/M - interaction diagram of the cross-section representing the results of three test series 100 Figure B.5 -- Envelope line for determining the section of the actual bending moment, Mda 103

Figure C.1 Coefficient kc() allowing for decrease of compressive strength, fck, of AAC at elevated temperature 110

!Figure C.2" 111

!Figure C.3" - Coefficient ks() allowing for decrease of characteristic strength fyk of tension and compression reinforcement 112

!Figure C.4" -- Sections of AAC components showing nominal axis distance a and nominal concrete cover c of reinforcement 114

!Figure C.5" -- Reduction of strength and cross-section for sections exposed to fire 120

!Figure C.6" -- Division of a wall, with both sides exposed to fire, into zones for use in calculation of strength reduction and az values 120

Figure CA.1 -- Stress-strain relationship of AAC under compression at elevated temperature 123

Figure CA.2 -- Stress-strain relationship of reinforcing steel at elevated temperature 125

Figure CB.1 -- Example of a dry joint in structures made of floor or roof components with cover (e.g. topping) preventing movement of air through the joint 126

Figure CB.2 -- Examples of mortar joints in structures made of floor or roof components 126

Figure CB.3 -- Example of dry joints with two sealing strips in structures made of horizontal wall components 127

Figure CB.4 -- Examples of thin layer mortar joints in structures made of vertical or horizontal wall components 128

Figure CC.1 -- Temperature profiles for AAC wall, floor and roof components with a dry density of 300 kg/m3 129

Figure CC.2 -- Temperature profiles for AAC wall, floor and roof components with a dry density of 400 kg/m3 130

Figure CC.3 -- Temperature profiles for AAC wall, floor and roof components with a dry density of 500 kg/m3 131

Figure CC.4 -- Temperature profiles for AAC wall, floor and roof components with a dry density of 600 kg/m3 132

Figure CC.5 -- Temperature profiles of the non exposed face of component for the determination of the criteria of the classification to fire, for a dry density of 300 and 600 kg/m 133

Figure CC.6 -- Temperature profiles in °C for AAC-beams (b x h = 150 mm x 200 mm) with a dry density of 300 kg/m , exposed on three sides to standard fire 133

Figure CC.7 -- Temperature profiles in °C for AAC-beams (b x h = 150 mm x 200 mm) with a dry density of 400 kg/m , exposed on three sides to standard fire 134

Figure CC.8 -- Temperature profiles in °C for AAC-beams (b x h = 150 mm x 200 mm) with a dry density of 500 kg/m , exposed on three sides to standard fire 135

Figure CC.9 -- Temperature profiles in °C for AAC-beams (b x h = 150 mm x 200 mm) with a dry density of 600 kg/m , exposed on three sides to standard fire 136

Figure CC.10 -- Temperature profiles in °C for AAC-beams (b x h = 300 mm x 400 mm) with a dry density of 300 kg/m , exposed on three sides to standard fire 137

Figure CC.11 -- Temperature profiles in °C for AAC-beams (b x h = 300 mm x 400 mm) with a dry density of 400 kg/m3 , exposed on three sides to standard fire 138

Figure CC.12 -- Temperature profiles in °C for AAC-beams (b x h = 300 mm x 400 mm) with a dry density of 500 kg/m3 , exposed on three sides to standard fire 139

Figure CC.13 -- Temperature profiles in °C for AAC-beams (b x h = 300 mm x 400 mm) with a dry density of 600 kg/m , exposed on three sides to standard fire 140

Figure E.1 -- Analysis of prestress by means of an assumed external force 148

Figure ZA.1 Example of CE marking with Method 1 170

Figure ZA.2 Example of CE marking with Method 2 171

Figure ZA.3a Example of CE marking with Method 3a 173

Figure ZA.3b Example of CE marking with Method 3b 175

Figure ZA.4 -- Example of simplified label 177

Tables Table 1 -- Density classes 24

!Table 2a" -- Compressive strength classes for AAC 25

!Table 2b Drying shrinkage classes for AAC" 27

Table 3 -- Creep classes 28

Table 4 -- Dry thermal conductivity 10dry of AAC for 50 % and 90 % of production with a confidence level of = 90 % (compiled according to EN 1745) 30

Table 5a List of steel grades for stainless reinforcing steel 31

Table 5b Mandrel diameter for the bending test 32

!Table 5c" -- Welding strength classes and welding strength factors kW 32

!Table 6 Bond classes" 33

Table 7 -- Prestress classes 34

Table 8 -- Dimensional tolerances of components 37

Table 9 -- Final shrinkage strains 0 for AAC components 37

Table 10 -- Thickness classes of structural components 39

Table 11 -- Exposure classes and protective measures related to environmental conditions 42

Table 12 -- Initial type-testing of the AAC components 47

Table 13 -- Testing of the finished product; AAC components for structural uses 50

Table 14 -- Testing of the finished product; AAC components for non-structural uses 53

Table A.1 -- Bond Classes 89

Table B.1 -- Design loadbearing capacity Rcd of components 102

Table C.1 -- Thermal conductivity of AAC () at elevated temperature 111

Table C.2 -- Minimum wall thickness of non loadbearing AAC walls with a dry density between 350 kg/m and 700 kg/m 114

Table C.3a -- Minimum wall thickness and axis distance amin for separating loadbearing AAC walls. AAC dry density 350 kg/m3 to 700 kg/m and structural or non-structural reinforcement for resistance to fire REI 115

Table C.3b -- Minimum wall thickness and minimum axis distance amin for non separating loadbearing AAC walls supported on at least two opposite ends of the components. AAC dry density 350 kg/m3 to 700 kg/m³ and structural or non-structural reinforcement for resistance to fire R 115

Table C.4 -- Minimum dimensions (height hmin and width bmin) in mm and minimum axis distance amin in mm to the bottom side and to the vertical sides of AAC beams in relation to the maximum span length 116 Table C.5 -- Minimum thickness hmin in mm and minimum axis distance amin in mm of AAC floor and roof components in relation to maximum span length 117

Table C.6 -- Reduction of the dimensions of AAC cross-section from fire exposed surfaces 122

Table CA.1 --Values for the parameters of stress-strain relationship of AAC in compression at elevated temperature 123

Table CA.2 -- Values for the parameters of stress-strain relationship of reinforcing steel at elevated temperature 124

Table CC.1 141

Table CC.2 141

Table CD.1 -- Minimum wall thickness and minimum axis distance amin of AAC walls with mechanical impact supported on at least two opposite ends; AAC dry density 450 kg/m3 to 700 kg/m3 with structural or non structural reinforcement for resistance to fire REI-M and EI-M 142

Table CD.2 -- Minimum amount of reinforcement for AAC components used in walls with mechanical impact 143

Table D.1 -- Safety parameter for failure type 144

Table D.2 -- Safety parameter for accuracy when determining the material parameter 144

Table D.3 -- Safety parameters depending on variation 145

Table D.4 -- Partial safety factors 145

Table F.1 -- Control factor kn as a function of samples n with a fractile value of 5 % (p = 0,95) and a confidence level of 0,75 (using bayesian procedures with "vague" prior distribution) and under the assumption that the safety level (Annex D) is based on a summarised variation of VR = 0,10 153

Table F.2-- Coefficient ks as a function of samples n with a fractile value of 5 % (p = 0,95) and a confidence level 0,75 (using bayesian procedures with "vague" prior distribution) 153

Table ZA.1a -- Harmonised clauses for loadbearing wall components 156

Table ZA.1b -- Harmonised clauses for retaining wall components 157

Table ZA.1c -- Harmonised clauses for roof components 158

Table ZA.1d -- Harmonised clauses for floor components 159

Table ZA.1e -- Harmonised clauses for linear components 160

Table ZA.1f -- Harmonised clauses for non-loadbearing wall and noise barriers components 161

Table ZA.1g -- Harmonised clauses for cladding components 162

Table ZA.1h -- Harmonised clauses for small box culvert components 163

Table ZA.2a -- Systems of attestation of conformity 164

Table ZA.2b -- Assignation of evaluation of conformity tasks (for structural components) under system 2+1) 164

Table ZA.2c -- Assignation of evaluation of conformity tasks (for non structural or light structural components) under system 4 1) 165