

DIN EN 15683-1:2014-01 (E)

Glass in building - Thermally toughened soda lime silicate channel shaped safety glass - Part 1: Definition and description

Contents	Page
Foreword	3
Introduction	4
1 Scope	5
2 Normative references	5
3 Terms and definitions	5
4 Glass products	6
5 Fracture characteristics	6
6 Dimensions and tolerances	6
6.1 General	6
6.2 Dimensions and dimensional tolerances	6
6.2.1 Nominal thickness (c) and thickness tolerances	6
6.2.2 Width, flange height and length (sizes)	6
6.3 Shape	7
6.3.1 Flange deviation	7
6.3.2 Squareness of cut, q	8
6.3.3 Tolerances on shape	8
6.4 Flatness	8
6.4.1 General	8
6.4.2 Measurement of overall bow	9
6.4.3 Limitation on overall bow	10
7 Edge working of channel shaped glass before toughening	10
8 Fragmentation test	11
8.1 General	11
8.2 Dimensions and number of test specimens	11
8.3 Test procedure	11
8.4 Assessment of fragmentation	12
8.5 Minimum values from the particle count	12
8.6 Selection of the longest particle	13
8.7 Maximum length of longest particle	13
9 Other physical characteristics	13
9.1 Optical distortion	13
9.2 Anisotropy (iridescence)	13
9.3 Thermal durability	13
9.4 Profile bending strength	13
9.5 Allowable stress	14
9.6 Allowable deflection	14
10 Marking	14
Annex A (informative) Example of particle count	15
Bibliography	18