

DIN EN 1995-1-1/A2:2014-07 (E)

Eurocode 5: Design of timber structures - Part 1-1: General - Common rules and rules for buildings

| Contents | | Page |
|-----------------|---|-------------|
| | Foreword | 3 |
| 1 | Modifications to 1.2, Normative references | 4 |
| 2 | Modification to 1.6, Symbols used in EN 1995-1-1 | 4 |
| 3 | Modifications to 2.2.3, Serviceability limit states | 4 |
| 4 | Modification to 2.3.2.2, Load-duration and moisture influences on deformations | 4 |
| 5 | Modification to 4.2, Resistance to corrosion | 5 |
| 6 | Modification to 6.1.5, Compression perpendicular to the grain | 5 |
| 7 | Modification to 6.1.8, Torsion | 5 |
| 8 | Modification to 6.2.3, Combined bending and axial tension | 5 |
| 9 | Modification to 6.5.2, Beams with a notch at the support | 6 |
| 10 | Modification to 8.3.2, Axially loaded nails | 6 |
| 11 | Modifications to 8.4, Stapled connections | 6 |
| 12 | Modification to 8.6, Dowelled connections | 6 |
| 13 | Modifications to 8.7.1, Laterally loaded screws | 7 |
| 14 | Modification to 8.7.2, Axially loaded screws | 7 |
| 15 | Modifications to 8.8.5.1, Plate anchorage capacity | 8 |
| 16 | Modification to 8.8.5.2, Plate capacity | 8 |
| 17 | Modification to 8.9, Split ring and shear plate connectors | 9 |
| 18 | Modification to 8.10, Toothed -plate connectors | 9 |
| 19 | Modifications to Annex A | 10 |
| 20 | Modification to B.4, Maximum shear stress | 10 |