

ISO 3008-2:2014-04 (E)

Fire-resistance tests - Part 2: Lift landing door assemblies

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Test equipment	2
5	Test conditions	2
6	Test specimen	3
6.1	Size of specimen	3
6.2	Number of specimens	3
6.3	Supporting construction	3
6.4	Installation of specimen	3
6.5	Verification	4
7	Conditioning	5
8	Clearances	5
9	Functionality test	5
10	Application of instrumentation	5
10.1	Temperature measurements	5
10.2	Pressure measurements	6
10.3	Gas flow measurement	7
10.4	CO ₂ concentration	7
10.5	Heat-flux measurement	7
10.6	Deflection	7
11	Test procedure	7
11.1	Gap measurements	7
11.2	Functionality test	11
11.3	Flow measurement verification	11
11.4	Fire test	12
12	Performance criteria	12
12.1	Integrity (E)	12
12.2	Insulation (I)	12
12.3	Radiation (W)	12
13	Termination of the test	12
14	Test report	13
15	Field of direct application of the test results	13

Annex A (normative) Description of the canopy and measuring system	14
Annex B (normative) Standard supporting construction	17
Annex C (normative) Verification procedure for the leakage rate measurement	18
Annex D (normative) Calculation of leakage rate	19
Annex E (informative) Extrapolation rule for the leakage rate for higher lift landing door assemblies	21
Annex F (informative) Interpreting the leakage rate curve	23
Annex G (informative) Marking information	24