

DIN EN 12966:2015-03 (E)

Road vertical signs - Variable message traffic signs

Contents		Page
Foreword		7
Introduction		9
1	Scope	10
2	Normative references	10
3	Terms and definitions	11
4	Product characteristics	15
4.1	Dimensions and tolerances requirements	15
4.2	General design requirement	15
4.3	Visual performance requirements of continuous VMS	15
4.4	Visual performance requirements of discontinuous VMS	15
4.5	Physical performance requirements	24
4.6	Dangerous substances	28
5	Testing, assessment and sampling methods	28
5.1	Test sequence	28
5.2	Durability	29
5.3	Test modules	29
5.4	Physical performance test methods	31
5.5	Visual performance test methods	36
6	Assessment and verification of constancy of performance (AVCP)	45
6.1	General	45
6.2	Type testing	45
6.3	Factory production control (FPC)	51
7	Classification and designation	57
7.1	General	57
7.2	Continuous retro-reflective VMS	57
7.3	Continuous, externally illuminated retro-reflective VMS	58
7.4	Discontinuous VMS	59
8	Marking, labelling and packaging	60
9	Product information	60
Annex A (normative) Equivalent area		61
A.1	General	61
A.2	Calculation of the luminance	61
A.3	Calculation of non-matrix equivalent areas	64
A.3.1	Equivalent area for a line of elements	64
A.3.2	Equivalent area for a symbol fully populated with elements	65
A.3.3	Equivalent area for a symbol partially populated with elements	65
Annex B (normative) VMS performance declaration codes for marking		67
B.1	General	67

B.2	Code for continuous retro-reflective VMS	67
B.3	Code for externally illuminated continuous retro-reflective VMS	67
B.4	Code for discontinuous VMS	68
Annex L (informative) Terminology used in this European Standard		69
Annex M (informative) Guidance on graphics for discontinuous light emitting signs		71
M.1	General	71
M.2	Apparent luminance of lines and letter strokes	71
M.2.1	General	71
M.2.2	Further technical explanation of Apparent luminance	72
M.3	VMS with colour inversion	73
M.4	VMS without colour inversion	78
Annex N (informative) Guidance on dimensions , luminance, beam width, legibility and efficiency for discontinuous VMS		80
N.1	General	80
N.2	Dimensions	80
N.2.1	General	80
N.2.2	Text	81
N.2.3	Circles	81
N.2.4	Triangles	82
N.3	Luminance and beam width classes	82
N.4	Beam width and distances of legibility	87
N.4.1	Group of VMS, centred above the road	87
N.4.2	Group of VMS, not centred above the road	88
N.4.3	Curved road sections	89
N.4.4	Limits of legibility due to vertical beam	90
N.4.5	Calculation of recognition time	92
N.4.5.1	General	92
N.4.5.2	Distances in metres per second at various speeds	92
N.4.5.3	Example of calculation of the recognition time	92
N.4.5.3.1	General	92
N.4.5.3.2	Using beam width class B2	93
N.4.5.3.3	Using beam width class B4	94
N.4.5.3.4	Using beam width class B6	95
N.4.5.4	Conclusions after calculation of recognition time	95
N.4.6	Luminance and luminance ratio	96
N.4.7	Beam width	96
N.5	Energy efficiency	96
Annex O (informative) Specific design issues		97
O.1	Finish	97
O.2	Front panels	97
O.3	Front screens	97
O.4	Appearance	97
O.5	Electrolytic compatibility	97
O.6	Protection against thermal overload	97
O.7	Physical security against unauthorised access	97
O.8	Interfaces between VMS, control, and higher order equipment	97
O.9	Diagnostic	97
Annex P (informative) Guidance for design of VMS messages		99
P.1	Design of VMS messages	99
P.2	Specifying text dimensions	100
Annex Q (informative) Technical documentation		102

Q.1	Sign enclosure	102
Q.2	Electrical equipment	102
Q.3	Mounting devices (if applicable)	102
Q.4	Retro-reflective and non retro-reflective components	102
Annex R (informative) Example of recommended summary of class combinations		104
Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Regulation		112
ZA.1 Scope and relevant characteristics		112
ZA.2 Procedure for AVCP of VMS		115
ZA.3 CE marking and labelling		119
Bibliography		128
Figures Page Figure 1 -- Chromaticity areas for the colour classes C1 and C2 plotted in the CIE 1931 chromaticity diagram		18
Figure 2 -- Examples of passed and failed luminance distributions		23
Figure 3 -- Examples of variable message traffic sign test modules in front view - a) and c) - and side view b)		30
Figure 4 -- Side elevation of the set-up for the measurement of luminance and luminance ratio		37
Figure 5 -- Layout examples for a test module and the positioning of the measuring area (circle) of the luminance meter		42
Figure A.1 -- Merging of elements		61
Figure A.2 -- Character with a regular orthogonal matrix of (5 × 8) elements		62
Figure A.3 -- Open line		64
Figure A.4 -- Closed line		64
Figure A.5 -- Example of symbol with an area fully populated with elements		65
Figure A.6 -- Example of symbol with an area partially populated with elements		66
Figure B.1 -- Code of performance classes of continuous retro-reflective VMS		67
Figure B.2 -- Code of performance classes of externally illuminated continuous retro-reflective VMS		68
Figure B.3 -- Code of performance classes of discontinuous VMS		68
Figure L.1 -- Parts of a VMS		69
Figure L.2 -- Test configuration		70
Figure M.1 -- A legend seen at short (left), longer (centre), and very long distance (right)		72
Figure M.2 -- Example for calculation of dimensions of circular mandatory VMS		76
Figure M.3 -- Example for calculation of dimensions of circular mandatory VMS		76
Figure M.4 -- Example for calculation of dimensions of a triangular warning VMS		77

Figure M.5 -- Example of VMS using (64 × 64) elements with colour inversion	78
Figure M.6 -- Example of VMS using (48 × 48) elements with colour inversion	78
Figure M.7 -- Example of VMS using (32 × 32) elements with colour inversion	78
Figure M.8 -- Example of VMS using (64 × 64) elements, no colour inversion	79
Figure M.9 -- Example of VMS using (48 × 48) elements, no colour inversion	79
Figure M.10 -- Example of VMS using (32 × 32) elements, no colour inversion	79
Figure N.1 -- Relation between classes	83
Figure N.2 -- Example of coverage by beam width class B1	84
Figure N.3 -- Example of coverage by beam width class B3	85
Figure N.4 -- Example of coverage by beam width class B6	86
Figure N.5 -- Legibility of group of VMS, centred on gantry above the road	87
Figure N.6 -- Legibility of group of VMS, mounted on cantilever aside the road	88
Figure N.7-- Legibility of group of VMS, mounted on cantilever aside the road	90
Figure N.8-- Legibility of group of VMS, mounted on cantilever aside the road	91
Figure P.1 -- Example of the design of the letter E in a regular orthogonal matrix	99
Figure P.2 -- Equivalent text dimensions using uppercase characters	100
Figure P.3 -- Equivalent text dimensions using upper- and lower-case characters	100
Figure P.4 -- Equivalent text dimensions of full matrix display using proportional character spacing	101
Figure R.1-- Example of summary of the characteristics of products	105
Figure R.2 -- Example 1 for visual performance class combination	107
Figure R.3 -- Example 2 for visual performance class combination	108
Figure R.4 -- Example 3 for visual performance class combination	110
Figure R.5 -- Example 4 for visual performance class combination	111
Figure ZA.1 -- Example of CE marking affixed to a continuous retro-reflective VMS	123
Figure ZA.2 -- Example of CE marking affixed to a continuous, externally illuminated retro-reflective VMS	124
Figure ZA.3 -- Example of CE marking affixed to a discontinuous VMS	125
Figure ZA.4 -- Example of CE marking affixed to a continuous retro-reflective VMS	126
Figure ZA.5 -- Example of CE marking affixed to a continuous, externally illuminated retro-reflective VMS	126
Figure ZA.6 -- Example of CE marking affixed to a discontinuous VMS	127
Tables Page Table 1 -- Class designation of the visual performance parameters of VMS	16

Table 2 -- Corner points (CIE 1931 chromaticity co-ordinates x, y) of the chromaticity areas for the colours of class C1	17
Table 3 -- Corner points (CIE 1931 chromaticity co-ordinates x, y) of the chromaticity areas for the colours of class C2	17
Table 4 -- Le and La luminance limits for white on reference axis	19
Table 5 -- Le and La luminance limits for yellow on reference axis	20
Table 6 -- Le and La luminance limits for orange on reference axis	20
Table 7 -- Le and La luminance limits for green on reference axis	20
Table 8 -- Le and La luminance limits for red on reference axis	21
Table 9 -- Le and La luminance limits for blue on reference axis	21
Table 10 -- Minimum luminance ratio values (LR) for various colours and classes R1, R2 and R3, at test angles on the reference axis and off the reference axis	22
Table 11 -- Beam width classes	23
Table 12 -- Class designation	24
Table 13 -- Temperature range classes	25
Table 14 -- Ingress protection level classes	26
Table 15 -- Effect of voltage interruption	27
Table 16 -- Operating voltage range, power-up activation and temporary overvoltage tests	31
Table 17 -- Frequency and voltage tests	31
Table 18 -- Impact test	32
Table 19 -- Vibration test	32
Table 20 -- Corrosion test	33
Table 21 -- Water ingress test - Severity	33
Table 22 -- Dust ingress test - Severity	33
Table 23 -- Temperature test	34
Table 24 -- Test angles (in degrees, with respect to the reference axis), used for the measurement of luminance under external illumination and luminance ratio	38
Table 25 -- Test angles (in degrees, with respect to the reference axis), used for the measurement of luminance without external illumination	38
Table 26 -- Test angles (in degrees, with respect to the reference axis), used for the measurement of beam width, and for uniformity of luminous intensity and colour of monochromatic elements	39
Table 27 -- Test angles (in degrees, with respect to the reference axis), used for the measurement of uniformity of luminous intensity and colour of elements formed by mixing colours	40
Table 28 -- Characteristics of continuous VMS	46

Table 29 -- Characteristics of discontinuous VMS	48
Table 30 -- Identification label	51
Table 31 -- Minimum frequency of testing continuous VMS for product testing and evaluation as part of FPC	53
Table 32 -- Minimum frequency of testing discontinuous VMS for product testing and evaluation as part of FPC	54
Table M.1 -- Parameters for mandatory signs using a red circle	74
Table M.2 -- Parameters for mandatory signs using a red triangle	75
Table N.1 -- Minimum dimensions of text (mm)	81
Table N.2 -- Minimum dimensions of circles (mm)	82
Table N.3 -- Minimum dimensions of triangles (mm)	82
Table N.4 -- Examples for applications of beam width classes	83
Table N.5 -- Examples for recognition time depending on character height, speed and vertical beam width	91
Table N.6 -- Conversion from speed unit km/h to m/s	92
Table ZA.1.1 -- Relevant clauses for continuous VMS	112
Table ZA.1.2 -- Relevant clauses for discontinuous VMS	114
Table ZA.2 -- System of AVCP	115
Table ZA.3 -- Assignment of AVCP tasks for VMS under system 1	116