

DIN EN 13022-1:2014-08 (E)

Glass in building - Structural sealant glazing - Part 1: Glass products for structural sealant glazing systems for supported and unsupported monolithic and multiple glazing

Contents		Page
Foreword		3
1	Scope	4
2	Normative references	7
3	Symbols, terminology, terms and definitions	8
3.1	Symbols	8
3.2	Terminology	9
3.3	Terms and definitions	10
4	Characteristics of glass products - requirements	12
4.1	Appropriate glass products	12
4.2	Dimensional tolerances	12
4.3	Glass shapes - Curved glass	12
4.4	Corners, notches and holes	13
5	Verification of the suitability of glass products for use in SSG systems when exposed to UV radiation	14
5.1	General	14
5.2	Insulating glass unit (IGU)	14
5.2.1	Situation 1 (see Figure 2 of the Scope)	14
5.2.2	Situation 2 (see Figure 2 of the Scope)	14
5.2.3	Coated glass	15
5.2.4	Possibility to substitute the outer IGU seal - General case	16
5.2.5	Possibility to substitute the outer IGU seal - Case of unsupported glass: Further requirements	16
5.3	Monolithic glass or laminated glass, Situation 3 (see Figure 2)	16
5.4	Assessment of the adhesion between the sealant and the glass	16
5.4.1	Clear float	16
5.4.2	Coated glass	16
5.4.3	Enamelled glass	16
5.4.4	Patterned glass	17
6	Design	17
6.1	Calculation of the thickness of the glass	17
6.2	Calculation of the height of the outer sealant of the insulating glass unit for supported and unsupported glazing	17
6.2.1	Supported insulating glass unit	17
6.3	Calculation of the height of the outer sealant of the insulating glass unit for unsupported glazing	21
6.3.1	Calculation of the height regarding the relevant combined load of the wind, snow and self weight	21
6.3.2	Calculation of the height of the outer seal to bear the permanent shear loading	22
7	Minimum glass thickness	22
7.1	General case	22
7.2	Case of glass with worked edges	23

Annex A (informative) Assembly recommendations	25
A.1 Setting blocks for monolithic glass, laminated glass and insulating glass units	25
A.2 Water drainage from the system	28
Bibliography	29