DIN EN 1075:2015-03 (Engli sch)

Timber structures - Test methods - Joints made with punched metal plate fasteners

Contents

Page

Foreword 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 5

4 Symbols and abbreviations 7

5 Materials 7
5.1 Timber 7
5.2 Fasteners 7

6 Test methods 8
6.1 General 8
6.2 Conditioning 8
6.3 Fabrication of test pieces 8
6.4 Preparation of test pieces 9
6.4.1 Anchorage capacity and load-slip characteristics of contact surface and timber: load parallel to grain 9
6.4.2 Anchorage capacity and load-slip characteristics of contact surface of fastener and timber: load not parallel to grain 10
6.4.3 Fastener tension capacity 11
6.4.4 Fastener compression capacity 12
6.4.5 Fastener shear capacity 13
6.5 Procedure 13
6.5.1 Estimation of maximum load 13
6.5.2 Loading procedure 13
6.5.3 Maximum load 14
6.6 Expression of results 15
6.6.1 Anchorage capacity 15
6.6.2 Fastener tension capacity 15
6.6.3 Fastener compression capacity 15
6.6.4 Fastener shear capacity 16
6.7 Determination of characteristic values 16
6.8 Test report 16

Annex A (normative) Nail root test 17

A.1 Scope 17
A.2 Symbols 17
A.3 Test piece 17
A.4 Test method 17
A.5 Test results 17

Annex B (informative) Derivation of rotational stiffness of the contact surface of the fastener and timber 19

B.1 General 19
B.2 Background to the calculations 19
B.3 Calculations 19

Annex C (informative) Examples of properly located transducers 21

Annex D (informative) Examples of loading arrangement 22

D.1 Fastener shear capacity 22
D.2 Fastener anchorage capacity: load not parallel to grain, (see 6.4.2) 24

Bibliography 25