

DIN EN 1075:2015-03 (English)

Timber structures - Test methods - Joints made with punched metal plate fasteners

Contents		Page
Foreword		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	5
4	Symbols and abbreviations	7
5	Materials	7
5.1	Timber	7
5.2	Fasteners	7
6	Test methods	8
6.1	General	8
6.2	Conditioning	8
6.3	Fabrication of test pieces	8
6.4	Preparation of test pieces	9
6.4.1	Anchorage capacity and load-slip characteristics of contact surface and timber: load parallel to grain	9
6.4.2	Anchorage capacity and load-slip characteristics of contact surface of fastener and timber: load not parallel to grain	10
6.4.3	Fastener tension capacity	11
6.4.4	Fastener compression capacity	12
6.4.5	Fastener shear capacity	13
6.5	Procedure	13
6.5.1	Estimation of maximum load	13
6.5.2	Loading procedure	13
6.5.3	Maximum load	14
6.6	Expression of results	15
6.6.1	Anchorage capacity	15
6.6.2	Fastener tension capacity	15
6.6.3	Fastener compression capacity	15
6.6.4	Fastener shear capacity	16
6.7	Determination of characteristic values	16
6.8	Test report	16
Annex A (normative) Nail root test		17
A.1	Scope	17
A.2	Symbols	17
A.3	Test piece	17
A.4	Test method	17
A.5	Test results	17
Annex B (informative) Derivation of rotational stiffness of the contact surface of the fastener and timber		19
B.1	General	19
B.2	Background to the calculations	19
B.3	Calculations	19

Annex C (informative) Examples of properly located transducers	21
Annex D (informative) Examples of loading arrangement	22
D.1 Fastener shear capacity	22
D.2 Fastener anchorage capacity: load not parallel to grain, (see 6.4.2)	24
Bibliography	25