DIN EN 13164:2015-04 (E)

Thermal insulation products for buildings - Factory made extruded polystyrene foam (XPS) products - Specification (includes Amendment A1:2015)

Contents

Page

Foreword 5

1 Scope 7

2 Normative references 7

3 Terms, definitions, symbols, units, abbreviated terms 8
3.1 Terms and definitions 8
3.2 Symbols, units and abbreviated terms 9

4 Requirements 11
4.1 General 11
4.2 For all applications 12
4.2.1 Thermal resistance and thermal conductivity 12
4.2.2 Length, width, squareness, flatness 12
4.2.3 Thickness 13
4.2.4 Reaction to fire of the product as placed on the market 13
4.2.5 Durability characteristics 13
4.3 For specific applications 14
4.3.1 General 14
4.3.2 Dimensional stability under specified conditions 14
4.3.3 Deformation under specified compressive load and temperature conditions 14
4.3.4 Compressive stress or compressive strength 15
4.3.5 Tensile strength perpendicular to faces 15
4.3.6 Compressive creep 16
4.3.7 Water absorption 16
4.3.8 Freeze-thaw resistance 17
4.3.9 Water vapour transmission 17
4.3.10 Release of dangerous substances 18
4.3.11 Reaction to fire of the product in standardized assemblies simulating end-use applications 18
4.3.12 Continuous glowing combustion 18
4.3.13 Shear strength 18

5 Test methods 18
5.1 Sampling 18
5.2 Conditioning 18
5.3 Testing 19
5.3.1 General 19
5.3.2 Thermal resistance and thermal conductivity 19

6 Designation code 21

7 Assessment and Verification of the Constancy of Performance (AVCP) 22
7.1 General 22
7.2 Product Type Determination (PTD) 22
7.3 Factory Production Control (FPC) 22

8 Marking and labelling 22

Annex A (normative) **Determination of the declared values of thermal resistance and thermal conductivity** **24**
A.1 General **24**
A.2 Input data **24**
A.3 Declared values **24**
A.3.1 General **24**
A.3.2 Case where thermal resistance and thermal conductivity are declared **24**
A.3.3 Case where only thermal resistance is declared **25**
Annex B (normative) **[A1] Product type determination [A1] ([A1] PTD [A1]) and Factory production control (FPC)** **26**
Annex C (normative) **Determination of the aged values of thermal resistance and thermal conductivity** **30**
C.1 General **30**
C.2 Procedure for XPS foam without diffusion tight facings **30**
C.2.1 Principle **30**
C.2.2 Sample preparation **30**
C.2.3 Procedure **30**
C.3 Procedure for XPS foam for use with diffusion tight facing on both sides **31**
C.3.1 Principle **31**
C.3.2 Ageing procedure **31**
C.4 Determination of value after ageing: "aged value" **31**
C.4.1 Determination of aged value for XPS products without diffusion tight facings on both sides **31**
C.4.2 Determination of aged value for XPS products for use with diffusion tight facing on both sides **32**
C.5 Blowing agent **33**
C.6 Product grouping **33**
Annex D (normative) **XPS multi-layered insulation products** **34**
D.1 General **34**
D.2 Requirements **34**
D.2.1 For all applications **34**
D.2.2 For specific applications **35**
D.3 Test methods **35**
D.4 Evaluation of conformity **35**
Annex E (informative) **Additional properties** **36**
E.1 General **36**
E.2 Behaviour under cyclic loading **36**
E.3 Compressive modulus of elasticity **36**
E.4 Bending strength **36**
E.5 Determination of volume percentage of closed cells **36**

Annex F (informative) **Plan for cutting test specimen** 38

Annex ZA (informative) **[A1] Clauses of this European Standard addressing the provisions of the EU Construction Products Regulation [A1]** 40

ZA.1 Scope and relevant characteristics 40

ZA.2 Procedures for AVCP of factory made extruded polystyrene products 41

ZA.2.1 Systems of AVCP 41

ZA.2.2 Declaration of Performance (DoP) 45

ZA.3 CE Marking and labelling 48

Bibliography 50

Tables

Table 1 — Tolerances of length, width, squareness and flatness 13

Table 2 — Classes for thickness tolerances 13

Table 3 — Dimensional stability under specified conditions 14

Table 4 — Levels for deformation under specified compressive load and temperature conditions 15

Table 5 — Levels for compressive stress or compressive strength 15

Table 6 — Levels for tensile strength, perpendicular to faces 16

Table 7 — Levels for long term water absorption by total immersion 16

Table 8 — Levels for long term water absorption by diffusion 17

Table 9 — Test methods, test specimens and conditions 19

Table A.1 — Values for k for one sided 90 % tolerance interval with a confidence level of 90 % 25

Table B.1 — Minimum number of tests for !PTD" and minimum product testing frequencies 26

Table B.2 – Minimum product testing frequencies for the reaction to fire characteristics 28

Table E.1 — Test methods, test specimens, conditions and minimum testing frequencies 37

Table ZA.1 — Relevant clauses for factory made extruded polystyrene foam and intended use 40

Table ZA.2 — Systems of AVCP 42

Table ZA.3.1 — Assignment of AVCP tasks for factory made extruded polystyrene foam products under system 1 for reaction to fire and system 3 (see Table ZA.2) 42

Table ZA.3.2 — Assignment of AVCP tasks for factory made extruded polystyrene foam products under system 3 (see Table ZA.2) 44

Table ZA.3.3 — Assignment of AVCP tasks for factory made extruded polystyrene foam products under combined system 4 for reaction to fire and system 3 (see Table ZA.2) 44

Figures

Figure ZA.1 — Example CE marking information of products under AVCP system 3" 49