

DIN EN ISO 9972:2015-12 (E)

Thermal performance of buildings - Determination of air permeability of buildings - Fan pressurization method (ISO 9972:2015)

Contents		Page
European foreword		4
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms, definitions, and symbols	6
3.1	Terms and definitions	6
3.2	Symbols	8
4	Apparatus	9
4.1	General	9
4.2	Equipment	9
4.2.1	Air-moving equipment	9
4.2.2	Pressure-measuring device	9
4.2.3	Air flow rate measuring system	9
4.2.4	Temperature-measuring device	9
5	Measurement procedure	9
5.1	Measurement conditions	9
5.1.1	General	9
5.1.2	Measured extent	10
5.1.3	Time of measurement	10
5.2	Preparation	10
5.2.1	Building preparation methods	10
5.2.2	Heating, ventilation and air conditioning systems and other building equipment	10
5.2.3	Intentional openings in the envelope	11
5.2.4	Openings inside the measured extent	12
5.2.5	Air-moving equipment	12
5.2.6	Pressure measuring devices	12
5.3	Steps of the procedure	13
5.3.1	Preliminary check	13
5.3.2	Temperature and wind conditions	13
5.3.3	Zero-flow pressure difference	13
5.3.4	Pressure difference sequence	13
6	Expression of results	14
6.1	Reference values	14
6.1.1	Internal volume	14
6.1.2	Envelope area	14
6.1.3	Net floor area	15
6.2	Calculation of the air leakage rate	15
6.3	Derived quantities	18
6.3.1	General	18
6.3.2	Air change rate at reference pressure difference	18
6.3.3	Specific leakage rate (envelope)	18
6.3.4	Specific leakage rate (floor)	19
6.3.5	Effective leakage area	19
6.3.6	Specific effective leakage area (envelope)	19

6.3.7	Specific effective leakage area (floor)	19
7	Test report	20
8	Uncertainty	20
8.1	General	20
8.2	Reference value	21
8.3	Overall uncertainty	21
Annex A (informative) Description of equipment used to pressurize buildings		22
Annex B (informative) Dependence of air density on temperature, dew point, and barometric pressure		24
Annex C (informative) Recommended procedure for estimating uncertainty in derived quantities		20
Annex D (informative) Beaufort scale of wind (extract)		28
Annex E (informative) Detection of the leakage location		31