

ISO 1288-2:2016-02 (E)

Glass in building - Determination of the bending strength of glass - Part 2: Coaxial double-ring test on flat specimens with large test surface areas

| Contents | | Page |
|-----------------------|--|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Symbols | 2 |
| 5 | Principle of test method | 2 |
| 6 | Apparatus | 3 |
| 6.1 | Testing machine | 3 |
| 6.2 | Loading device | 4 |
| 6.2.1 | Ring load | 4 |
| 6.2.2 | Surface pressure regulator | 4 |
| 6.3 | Measuring instruments | 5 |
| 7 | Sample | 5 |
| 7.1 | Shape and dimensions of the specimens | 5 |
| 7.2 | Sampling and preparation of specimens | 5 |
| 7.2.1 | Cutting and handling | 5 |
| 7.2.2 | Conditioning | 5 |
| 7.2.3 | Examination | 6 |
| 7.2.4 | Adhesive film | 6 |
| 7.3 | Number of specimens | 6 |
| 8 | Procedure | 6 |
| 8.1 | Temperature | 6 |
| 8.2 | Humidity | 6 |
| 8.3 | Thickness measurement | 6 |
| 8.4 | Base plate | 6 |
| 8.5 | Positioning of specimen and loading ring | 6 |
| 8.6 | Load application | 7 |
| 8.7 | Loading rate | 7 |
| 8.8 | Location of the origin | 7 |
| 8.9 | Assessment of residual stresses | 7 |
| 9 | Evaluation | 8 |
| 9.1 | Limitation of the evaluation | 8 |
| 9.2 | Calculation of bending strength | 8 |
| 10 | Test report | 9 |
| Annex A (informative) | Example of a device for keeping the gas pressure, p , in line with the piston force, F | 11 |
| Bibliography | | 14 |