

# ISO 1288-5:2016-02 (E)

## Glass in building - Determination of the bending strength of glass - Part 5: Coaxial double ring test on flat specimens with sma II test surface areas

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Symbols .....</b>	<b>1</b>
<b>5</b>	<b>Principle of test method .....</b>	<b>2</b>
<b>6</b>	<b>Apparatus .....</b>	<b>3</b>
<b>6.1</b>	<b>Testing machine .....</b>	<b>3</b>
<b>6.2</b>	<b>Loading device .....</b>	<b>3</b>
<b>6.3</b>	<b>Measuring instruments .....</b>	<b>5</b>
<b>7</b>	<b>Sample .....</b>	<b>5</b>
<b>7.1</b>	<b>Shape and dimensions of specimens .....</b>	<b>5</b>
<b>7.2</b>	<b>Sampling and preparation of specimens .....</b>	<b>6</b>
<b>7.2.1</b>	<b>Cutting and handling .....</b>	<b>6</b>
<b>7.2.2</b>	<b>Conditioning .....</b>	<b>6</b>
<b>7.2.3</b>	<b>Examination .....</b>	<b>6</b>
<b>7.2.4</b>	<b>Adhesive film .....</b>	<b>6</b>
<b>7.3</b>	<b>Number of specimens .....</b>	<b>6</b>
<b>8</b>	<b>Procedure .....</b>	<b>6</b>
<b>8.1</b>	<b>Temperature .....</b>	<b>6</b>
<b>8.2</b>	<b>Humidity .....</b>	<b>6</b>
<b>8.3</b>	<b>Thickness measurement .....</b>	<b>6</b>
<b>8.4</b>	<b>Base plate .....</b>	<b>6</b>
<b>8.5</b>	<b>Positioning of specimen and loading ring .....</b>	<b>7</b>
<b>8.6</b>	<b>Load application .....</b>	<b>7</b>
<b>8.7</b>	<b>Location of the origin .....</b>	<b>7</b>
<b>8.8</b>	<b>Assessment of residual stresses .....</b>	<b>7</b>
<b>9</b>	<b>Evaluation .....</b>	<b>7</b>
<b>9.1</b>	<b>Limitation of the evaluation .....</b>	<b>7</b>
<b>9.2</b>	<b>Calculation of bending strength .....</b>	<b>8</b>
<b>10</b>	<b>Test report .....</b>	<b>8</b>
<b>Bibliography .....</b>		<b>9</b>