DIN EN 13108-9:2016-12 (E)

Bituminous mixtures - Material specifications - Part 9: Asphalt for Ultra-Thin Layer (AUTL)

Contents

Page

European foreword 4

Introduction 6

1 Scope 7

2 Normative references 7

3 Terms, definitions, symbols and abbreviations 8
3.1 Terms and definitions 8
3.2 Symbols and abbreviations 10

4 Requirements for constituent materials 10
4.1 General 10
4.2 Binder 10
4.2.1 General 10
4.2.2 Selection of binder 11
4.3 Aggregates 11
4.3.1 Coarse aggregate 11
4.3.2 Fine aggregate 11
4.3.3 All-in aggregates 12
4.3.4 Added filler 12
4.4 Reclaimed asphalt 12
4.5 Additives 12

5 Requirements for the mixture 12
5.1 General 12
5.2 Composition, grading, binder content 13
5.2.1 Composition 13
5.2.2 Grading 13
5.2.3 Minimum binder content 15
5.3 Properties 15
5.3.1 Specimens 15
5.3.2 Void content 15
5.3.3 Water sensitivity 17
5.3.4 Low temperature properties 17
5.3.5 Friction after polishing 18
5.3.6 Coating and homogeneity 19
5.3.7 Reaction to fire 19
5.3.8 Resistance to fuel for application on airfields 19
5.3.9 Resistance to de-icing fluid for application on airfields 20
5.4 Temperature of the mixture 20
5.5 Regulated dangerous substances 21
5.6 Conflicting requirements 21

6 Assessment and verification of constancy of performance -- AVCP 22

7 Identification 22

Annex A (normative) Calculations of the penetration or the softening point of the binder of a mixture when reclaimed asphalt is used 23

A.1 General 23
A.2 Calculation of the penetration of the binder of a mixture 23
A.3 Calculation of the softening point of the binder of a mixture 23

Annex ZA (informative) Relationship of this European Standard with Regulation (EU) No. 305/2011 25

ZA.1 Scope and relevant characteristics 25

ZA.2 System of Assessment and Verification of Constancy of Performance (AVCP) 26

ZA.3 Assignment of AVCP tasks 27

Bibliography 30