

DIN EN 13108-9:2016-12 (E)

Bituminous mixtures - Material specifications - Part 9: Asphalt for Ultra-Thin Layer (AUTL)

Contents		Page
European foreword		4
Introduction		6
1	Scope	7
2	Normative references	7
3	Terms, definitions, symbols and abbreviations	8
3.1	Terms and definitions	8
3.2	Symbols and abbreviations	10
4	Requirements for constituent materials	10
4.1	General	10
4.2	Binder	10
4.2.1	General	10
4.2.2	Selection of binder	11
4.3	Aggregates	11
4.3.1	Coarse aggregate	11
4.3.2	Fine aggregate	11
4.3.3	All-in aggregates	12
4.3.4	Added filler	12
4.4	Reclaimed asphalt	12
4.5	Additives	12
5	Requirements for the mixture	12
5.1	General	12
5.2	Composition, grading, binder content	13
5.2.1	Composition	13
5.2.2	Grading	13
5.2.3	Minimum binder content	15
5.3	Properties	15
5.3.1	Specimens	15
5.3.2	Void content	15
5.3.3	Water sensitivity	17
5.3.4	Low temperature properties	17
5.3.5	Friction after polishing	18
5.3.6	Coating and homogeneity	19
5.3.7	Reaction to fire	19
5.3.8	Resistance to fuel for application on airfields	19
5.3.9	Resistance to de-icing fluid for application on airfields	20
5.4	Temperature of the mixture	20
5.5	Regulated dangerous substances	21
5.6	Conflicting requirements	21
6	Assessment and verification of constancy of performance -- AVCP	22
7	Identification	22
Annex A (normative) Calculations of the penetration or the softening point of the binder of a mixture when reclaimed asphalt is used		23

A.1	General	23
A.2	Calculation of the penetration of the binder of a mixture	23
A.3	Calculation of the softening point of the binder of a mixture	23
Annex ZA (informative) Relationship of this European Standard with Regulation (EU) No. 305/2011		25
ZA.1	Scope and relevant characteristics	25
ZA.2	System of Assessment and Verification of Constancy of Performance (AVCP)	26
ZA.3	Assignment of AVCP tasks	27
Bibliography		30