ISO 3008-3:2016-05 (E)

Fire resistance tests - Part 3: Door and shutter assemblies horizontally oriented

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Test equipment 2

5 Test conditions 2

6 Test specimen 2
6.1 Size of specimen 2
6.2 Design of specimen 2
6.3 Verification 3

7 Installation of test specimen 3
7.1 General 3
7.2 Supporting construction 3
7.3 Test construction 3
7.3.1 Associated and supporting construction 3
7.3.2 Associated construction 4
7.3.3 Supporting construction 4
7.4 Gaps 4

8 Conditioning 4
8.1 Moisture content 4
8.2 Mechanical 4

9 Application of instrumentation 4
9.1 Temperature measurements 4
9.1.1 Furnace temperature measuring instrument 4
9.1.2 Unexposed face thermocouples 5
9.2 Maximum temperature 6
9.3 Pressure measurements 6
9.4 Heat flux measurement 6
9.4.1 General 6
9.4.2 Apparatus 7
9.4.3 Procedure 7
9.4.4 Measurement 8
9.5 Loading 8
9.6 Deflection 8

10 Test procedure 8
10.1 Gap measurements 9
10.2 Test Measurements 9

11 Performance criteria 9
11.1 Integrity 9

11.2 Insulation 9
11.3 Loadbearing capacity 9

12 Test report 10

13 Field of direct application of test results 10
13.1 General 10
13.2 Timber constructions 11
13.3 Steel constructions 11
13.4 Glazed constructions 11
13.5 Fixings/hardware 11

Annex A (normative) Conditioning requirements for supporting constructions 13

Annex B (informative)Estimationofradiantheatfluxusingmeasuredsurfacetemperature and Stefan-Boltzmann law 14