

ISO 3008-3:2016-05 (E)

Fire resistance tests - Part 3: Door and shutter assemblies horizontally oriented

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Test equipment	2
5	Test conditions	2
6	Test specimen	2
6.1	Size of specimen	2
6.2	Design of specimen	2
6.3	Verification	3
7	Installation of test specimen	3
7.1	General	3
7.2	Supporting construction	3
7.3	Test construction	3
7.3.1	Associated and supporting construction	3
7.3.2	Associated construction	4
7.3.3	Supporting construction	4
7.4	Gaps	4
8	Conditioning	4
8.1	Moisture content	4
8.2	Mechanical	4
9	Application of instrumentation	4
9.1	Temperature measurements	4
9.1.1	Furnace temperature measuring instrument	4
9.1.2	Unexposed face thermocouples	5
9.2	Maximum temperature	6
9.3	Pressure measurements	6
9.4	Heat flux measurement	6
9.4.1	General	6
9.4.2	Apparatus	7
9.4.3	Procedure	7
9.4.4	Measurement	8
9.5	Loading	8
9.6	Deflection	8
10	Test procedure	8
10.1	Gap measurements	9
10.2	Test Measurements	9
11	Performance criteria	9
11.1	Integrity	9

11.2	Insulation	9
11.3	Loadbearing capacity	9
12	Test report	10
13	Field of direct application of test results	10
13.1	General	10
13.2	Timber constructions	11
13.3	Steel constructions	11
13.4	Glazed constructions	11
13.5	Fixings/hardware	11
Annex A (normative) Conditioning requirements for supporting constructions		13
Annex B (informative) Estimation of radiant heat flux using measured surface temperature and Stefan-Boltzmann law		14