

ISO 3008-3:2016-05 (E)

Fire resistance tests - Part 3: Door and shutter assemblies horizontally oriented

| Contents | | Page |
|--|----|------|
| Foreword | v | |
| Introduction | vi | |
| 1 Scope | 1 | |
| 2 Normative references | 1 | |
| 3 Terms and definitions | 1 | |
| 4 Test equipment | 2 | |
| 5 Test conditions | 2 | |
| 6 Test specimen | 2 | |
| 6.1 Size of specimen | 2 | |
| 6.2 Design of specimen | 2 | |
| 6.3 Verification | 3 | |
| 7 Installation of test specimen | 3 | |
| 7.1 General | 3 | |
| 7.2 Supporting construction | 3 | |
| 7.3 Test construction | 3 | |
| 7.3.1 Associated and supporting construction | 3 | |
| 7.3.2 Associated construction | 4 | |
| 7.3.3 Supporting construction | 4 | |
| 7.4 Gaps | 4 | |
| 8 Conditioning | 4 | |
| 8.1 Moisture content | 4 | |
| 8.2 Mechanical | 4 | |
| 9 Application of instrumentation | 4 | |
| 9.1 Temperature measurements | 4 | |
| 9.1.1 Furnace temperature measuring instrument | 4 | |
| 9.1.2 Unexposed face thermocouples | 5 | |
| 9.2 Maximum temperature | 6 | |
| 9.3 Pressure measurements | 6 | |
| 9.4 Heat flux measurement | 6 | |
| 9.4.1 General | 6 | |
| 9.4.2 Apparatus | 7 | |
| 9.4.3 Procedure | 7 | |
| 9.4.4 Measurement | 8 | |
| 9.5 Loading | 8 | |
| 9.6 Deflection | 8 | |
| 10 Test procedure | 8 | |
| 10.1 Gap measurements | 9 | |
| 10.2 Test Measurements | 9 | |
| 11 Performance criteria | 9 | |
| 11.1 Integrity | 9 | |

| | | |
|------|--|----|
| 11.2 | Insulation | 9 |
| 11.3 | Loadbearing capacity | 9 |
| 12 | Test report | 10 |
| 13 | Field of direct application of test results | 10 |
| 13.1 | General | 10 |
| 13.2 | Timber constructions | 11 |
| 13.3 | Steel constructions | 11 |
| 13.4 | Glazed constructions | 11 |
| 13.5 | Fixings/hardware | 11 |
| | Annex A (normative) Conditioning requirements for supporting constructions | 13 |
| | Annex B (informative) Estimation of radiant heat flux using measured surface temperature and Stefan-Boltzmann law | 14 |