

DIN EN 16681:2016-12 (E)

Steel static storage systems - Adjustable pallet racking systems - Principles for seismic design

Contents		Page
European foreword		5
0	Introduction	5
1	Scope	8
2	Normative references	8
3	Terms and definitions	9
4	Symbols and abbreviations	10
4.1	Symbols	10
4.2	Abbreviations	12
5	Performance requirements and compliance criteria	13
5.1	Applicability	13
5.2	Performance requirements	13
5.2.1	No collapse requirement	13
5.2.2	Damage limitation requirement	13
5.2.3	Movement of unit loads	13
6	Ground conditions and seismic action	14
6.1	General	14
6.2	Damping	14
6.3	Importance factor I	14
6.4	Horizontal component of the seismic action	15
6.5	Vertical component of the seismic action	15
6.6	Design ground displacement	15
6.7	Racks supported by suspended floors	16
7	Methods of analysis	16
7.1	General	16
7.2	Limitation of the vertical load referred to the critical Euler Load	16
7.3	Inter-storey drift sensitivity coefficient	16
7.4	Analysis procedures	17
7.4.1	General	17
7.4.2	Second order effects	17
7.4.3	Lateral Force Method of Analysis (LFMA)	18
7.4.4	Modal Response Spectrum Analysis (MRSA)	20
7.4.5	Large Displacement Method of Analysis (LDMA)	20
7.4.6	Combination of the effects of the components of the seismic action	20
7.4.7	Displacements calculation	21
7.5	Design parameters for seismic analysis	21
7.5.1	General	21
7.5.2	Design spectrum modification factors	21
7.5.3	Unit load-beam friction coefficients	22
7.5.4	Design seismic weight of the unit load	23
7.5.5	Unit load weight modification factor	23
7.5.6	Other seismic weights	24
7.5.7	Weight of the seismic masses	24
7.5.8	Position of the centre of gravity of the unit load	24

7.5.9	Positioning tolerances	26
7.5.10	Structural regularity criteria	26
7.6	Modelling assumptions for structural analysis	27
7.6.1	Sub-modelling	27
7.6.2	Distribution of the masses	27
7.6.3	Specific modelling requirements for the analysis	28
7.6.4	Moment redistribution near the upright's base due to the floor reaction	29
8	Specific rules	31
8.1	Design concepts	31
8.1.1	General	31
8.1.2	Materials	31
8.1.3	Structural systems	32
8.1.4	Regularity criteria	32
8.1.5	Unbraced racks	38
8.1.6	Rules for the design of low dissipative structures	39
8.1.7	Rules for the design of dissipative structures	39
8.1.8	Anchoring conditions	39
8.2	Structural systems withstanding the seismic action	40
8.3	Structural types and behaviour factor	41
8.3.1	Upright frames	41
8.3.2	Moment resisting frames	42
8.3.3	Racks with vertical bracings in down aisle direction	44
9	Seismic analysis and design	47
9.1	Actions	47
9.1.1	Actions to be considered simultaneously with earthquake	47
9.1.2	Actions not to be considered simultaneously with earthquake	47
9.2	Safety Verifications	48
9.2.1	Ultimate limit states	48
9.2.2	Movements of the unit loads	49
9.3	Pallet beam design	50
9.3.1	Actions on pallet beams	50
9.3.2	Buckling length in the horizontal plane	51
9.3.3	Correction coefficient for horizontal bending	52
9.3.4	Buckling length factor in the vertical plane	52
9.3.5	Beam design check	52
Annex A (informative)	Analysis methods including second order effects	54
Annex B (normative)	Evaluation of the unit load -- beam friction coefficient	61
Annex C (informative)	Principles for modelling the unit load masses	66
Annex D (informative)	Simplified method to evaluate the influence of the centre of gravity of the pallet regarding the beam level	69
Annex E (informative)	Principles for the design of racks supported by floors	70
Annex F (normative)	Additional detailing rules for dissipative elements (Concept B)	72
Annex G (normative)	Testing procedure for beam-upright and floor connections for dissipative design (concept B)	73
Annex H (informative)	Assessment of the stability of the unit load	76
Annex I (informative)	Data to be exchanged between the Specifier/End User and the Rack's Supplier	78
Annex J (normative)	Complementary rules to EN 15635	79

Annex K (informative) Complementary rules to EN 15629 -- Warehouse environmental condition category 80

Annex L (informative) A-deviations 81

Bibliography 83