DIN EN ISO 10211:2018-03 (E)

Thermal bridges in building construction - Heat flows and surface temperatures - Detailed calculations (ISO 10211:2017)

Contents

Page

European foreword ... **4**

Foreword ... **6**

Introduction ... **7**

1 Scope ... **10**

2 Normative references ... **10**

3 Terms and definitions ... **11**

4 Symbols and subscripts ... **16**
4.1 Symbols ... 16
4.2 Subscripts ... 16

5 Description of the method ... **17**
5.1 Output ... 17
5.2 General description ... 17

6 Output data and input data ... **17**
6.1 Output data ... 17
6.2 Calculation time intervals ... 18
6.3 Input data ... 18

7 Modelling of the construction ... **18**
7.1 Dimension systems ... 18
7.2 Rules for modelling ... 18
7.2.1 General ... 18
7.2.2 Cut-off planes for a 3-D geometrical model for calculation of total heat flow and/or surface temperatures ... 18
7.2.3 Cut-off planes for a 2-D geometrical model ... 20
7.2.4 Cut-off planes in the ground ... 21
7.2.5 Periodic heat flows via the ground ... 22
7.2.6 Adjustments to dimensions ... 22
7.2.7 Auxiliary planes ... 24
7.2.8 Quasi-homogeneous layers and materials ... 24
7.3 Conditions for simplifying the geometrical model ... 24
7.3.1 General ... 24
7.3.2 Conditions for adjusting dimensions to simplify the geometrical model ... 25
7.3.3 Conditions for using quasi-homogeneous material layers to simplify the geometrical model ... 26

8 Input data specifications ... **29**
8.1 General ... 29
8.2 Thermal conductivities of materials ... 30
8.3 Surface resistances ... 30
8.4 Boundary temperatures ... 30
8.5 Thermal conductivity of quasi-homogeneous layers ... 30
8.6 Equivalent thermal conductivity of air cavities ... 30
8.7 Determining the temperature in an adjacent unheated room ... 31

9 Calculation method ... **31**
9.1 Solution technique ... 31
9.2 Calculation rules ... 31
9.2.1 Heat flows between material cells and adjacent environment ... 31
9.2.2 Heat flows at cut-off planes ... 31
9.2.3 Solution of the formulae ... 31
9.2.4 Calculation of the temperature distribution ... 32

10 Determination of thermal coupling coefficients and heat flow rate from 3-D calculations 32
10.1 Two boundary temperatures, unpartitioned model 32
10.2 Two boundary temperatures, partitioned model 32
10.3 More than two boundary temperatures 33

11 Calculations using linear and point thermal transmittances from 3-D calculations 34
11.1 Calculation of thermal coupling coefficient 34
11.2 Calculation of linear and point thermal transmittances 34

12 Determination of thermal coupling coefficient, heat flow rate and linear thermal transmittance from 2-D calculations 35
12.1 Two boundary temperatures 35
12.2 More than two boundary temperatures 35
12.3 Determination of the linear thermal transmittance 36
12.4 Determination of the linear thermal transmittance for wall/floor junctions 36
12.4.1 All cases 36
12.4.2 Option A 36
12.4.3 Option B 38
12.5 Determination of the external periodic heat transfer coefficient for ground floors 40

13 Determination of the temperature at the internal surface 41
13.1 Determination of the temperature at the internal surface from 3-D calculations 41
13.1.1 Two boundary temperatures 41
13.1.2 More than two boundary temperatures 41
13.2 Determination of the temperature at the internal surface from 2-D calculations 42
13.2.1 Two boundary temperatures 42
13.2.2 Three boundary temperatures 42

14 Report 42
14.1 Input data 42
14.2 Output data 43
14.2.1 General 43
14.2.2 Calculation of the heat transmission using the thermal coupling coefficient 43
14.2.3 Calculation of the surface temperatures using weighting factors 43
14.2.4 Additional output data 43
14.2.5 Estimate of error 44

Annex A (normative) **Input and method selection data sheet — Template 45**

Annex B (informative) **Input and method selection data sheet — Default choices 47**

Annex C (normative) **Validation of calculation methods 49**

Annex D (normative) **Examples of the determination of the linear and point thermal transmittances 56**

Annex E (normative) **Determination of values of thermal coupling coefficient and temperature weighting factor for more than two boundary temperatures 59**

Bibliography 64