

DIN EN 16809-2:2017-04 (E)

Therma I insulation products of buildings - In-situ formed products from loose-fill expanded polystyrene (EPS) beads and bonded expanded polystyrene beads - Part 2: Specification for the bonded and loose-fill products after installation

Contents		Page
European foreword		4
1	Scope	5
2	Normative references	5
3	Terms, definitions, symbols and abbreviations	5
3.1	Terms and definitions	5
3.2	Symbols and abbreviations	6
4	Requirements	6
4.1	General	6
4.2	Suitability of the building for the installation of the product	6
4.3	In situ measurements and calculations	6
4.3.1	General	6
4.3.2	The installed thermal resistance of masonry cavity wall and frame construction insulation	7
5	Installation checks	7
5.1	Average cavity width	7
5.2	Machine output	7
5.3	Installed volume	7
5.4	Thermal resistance of installed masonry cavity wall and frame construction installation ...	7
6	Guidelines for installation	8
7	Installer s declaration	8
Annex A (normative) Masonry cavity walls - Determination of average cavity width		9
A.1	Procedure	9
A.2	Calculation	9
Annex B (normative) Masonry cavity walls and frame constructions - Flow check procedures		10
B.1	Apparatus	10
B.2	Procedure	10
Annex C (normative) Masonry cavity walls - Use of endoscope to check adequacy of fill		11
C.1	Selection of inspection positions by the inspector	11
C.2	Action to be taken by the inspector	11
Annex D (normative) Guidance for the installer - Suitability of the building, training, pre- checks and installation declaration		12
D.1	Masonry cavity walls	12
D.1.1	Suitability of the building to receive the insulation	12
D.1.2	Suitability of the building to receive the insulation	12

D.1.3	Installation procedure	13
D.2	Frame constructions (new build walls)	13
D.2.1	Suitability of the building to receive the insulation	13
D.2.2	Control tests made by the installer when preparing the product on site	14
D.2.3	Installation procedure	14
D.2.4	An example of a declaration form for use by the installer	14
	Bibliography	15