

# DIN EN 14303:2016-08 (E)

## Thermal insulation products for building equipment and industrial installations - Factory made mineral wool (MW) products - Specification

---

<b>Contents</b>		<b>Page</b>
European foreword .....		3
<b>1</b>	<b>Scope .....</b>	<b>5</b>
<b>2</b>	<b>Normative references .....</b>	<b>5</b>
<b>3</b>	<b>Terms, definitions, symbols, units and abbreviated terms .....</b>	<b>7</b>
<b>3.1</b>	<b>Terms and definitions .....</b>	<b>7</b>
<b>3.2</b>	<b>Symbols, units and abbreviated terms .....</b>	<b>9</b>
<b>4</b>	<b>Requirements .....</b>	<b>10</b>
<b>4.1</b>	<b>General .....</b>	<b>10</b>
<b>4.2</b>	<b>For all applications .....</b>	<b>10</b>
<b>4.3</b>	<b>For specific applications .....</b>	<b>14</b>
<b>5</b>	<b>Test methods .....</b>	<b>16</b>
<b>5.1</b>	<b>Sampling .....</b>	<b>16</b>
<b>5.2</b>	<b>Conditioning .....</b>	<b>16</b>
<b>5.3</b>	<b>Testing .....</b>	<b>16</b>
<b>6</b>	<b>Designation code .....</b>	<b>19</b>
<b>7</b>	<b>Assessment and Verification of the Constancy of Performance (AVCP) .....</b>	<b>19</b>
<b>7.1</b>	<b>General .....</b>	<b>19</b>
<b>7.2</b>	<b>Product Type Determination (PTD) .....</b>	<b>20</b>
<b>7.3</b>	<b>Factory Production Control (FPC) .....</b>	<b>20</b>
<b>8</b>	<b>Marking and labelling .....</b>	<b>20</b>
<b>Annex A (normative) Factory production control .....</b>		<b>21</b>
<b>Annex B (informative) Additional Properties .....</b>		<b>25</b>
<b>B.1</b>	<b>General .....</b>	<b>25</b>
<b>B.2</b>	<b>Density .....</b>	<b>25</b>
<b>B.3</b>	<b>Flatness .....</b>	<b>25</b>
<b>B.4</b>	<b>Airflow resistivity .....</b>	<b>25</b>
<b>B.5</b>	<b>Dynamic stiffness .....</b>	<b>25</b>
<b>Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Regulation .....</b>		<b>27</b>
<b>ZA.1 Scope and relevant characteristics .....</b>		<b>27</b>
<b>ZA.2 Procedures for AVCP of factory made mineral wool products .....</b>		<b>29</b>
<b>ZA.3 CE Marking and labelling .....</b>		<b>36</b>
<b>Bibliography .....</b>		<b>38</b>