

ISO 22476-15:2016-08 (E)

Geotechnical investigation and testing - Field testing - Part 15: Measuring while drilling

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Symbols | 2 |
| 5 | Equipment | 3 |
| 5.1 | General | 3 |
| 5.2 | Drilling equipment | 4 |
| 5.3 | Measuring system | 4 |
| 5.3.1 | General | 4 |
| 5.3.2 | Sensors for hydraulic pressures | 5 |
| 5.3.3 | Measuring system for penetration length | 5 |
| 5.3.4 | Measuring system for flushing medium flow | 5 |
| 5.3.5 | Measuring system for rotational speed | 5 |
| 5.3.6 | Measuring of hammering energy | 6 |
| 5.3.7 | Reflected vibrations | 6 |
| 5.3.8 | Time | 6 |
| 5.4 | Selection of measured parameters | 6 |
| 5.5 | Factors influencing MWD results | 7 |
| 5.5.1 | Tool influence | 7 |
| 5.5.2 | Drilling rig influence | 7 |
| 5.5.3 | Operator influence | 7 |
| 6 | Test procedures | 7 |
| 6.1 | General | 7 |
| 6.2 | Position and level of drill rig | 8 |
| 6.3 | Preparation of the measurement | 8 |
| 6.4 | Drilling procedure | 8 |
| 6.5 | Frequency of logging parameters | 9 |
| 6.6 | Registration of penetration length | 9 |
| 6.7 | Test completion | 9 |
| 6.8 | Equipment checks and calibrations | 10 |
| 7 | Test results | 10 |
| 7.1 | General | 10 |
| 7.2 | Calculated parameters | 10 |
| 7.2.1 | General | 10 |
| 7.2.2 | Penetration rate | 10 |
| 7.2.3 | Down-thrust pressure | 10 |
| 7.2.4 | Net down-thrust pressure | 11 |
| 7.2.5 | Flushing medium pressure | 11 |
| 7.2.6 | Drill head rotational torque | 11 |
| 8 | Reporting | 12 |

| | | |
|-----|---|----|
| 8.1 | General | 12 |
| 8.2 | Reporting of test results | 12 |
| | Annex A (informative) Application of drilling parameters | 14 |
| | Annex B (informative) Graphical presentation of drilling parameters | 20 |
| | Bibliography | 22 |