

DIN EN 413-2:2016-12 (E)

Masonry cement - Part 2: Test methods

| Contents | | Page |
|-------------------------|---|-------------|
| European foreword | | 4 |
| Introduction | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | General requirements for testing | 6 |
| 3.1 | Laboratory | 6 |
| 3.2 | Manufacturing tolerances for test equipment | 6 |
| 3.2.1 | Dimensions | 6 |
| 3.2.2 | Mass | 6 |
| 3.3 | Tolerances for test equipment in use | 6 |
| 3.4 | Number of tests | 7 |
| 4 | Determination of setting time | 7 |
| 4.1 | General | 7 |
| 4.2 | Method A | 7 |
| 4.3 | Method B | 7 |
| 4.3.1 | Test principle | 7 |
| 4.3.2 | Initial setting time procedure | 7 |
| 4.3.3 | Report - initial setting time | 8 |
| 4.3.4 | Final setting time procedure | 8 |
| 4.3.5 | Report - final setting time | 8 |
| 4.3.6 | Repeatability and reproducibility | 8 |
| 5 | Preparation of standard mortar | 8 |
| 5.1 | Principle | 8 |
| 5.2 | Consistence of fresh mortar by plunger apparatus (reference method) | 8 |
| 5.2.1 | Apparatus | 8 |
| 5.2.2 | Procedure | 9 |
| 5.2.3 | Reproducibility | 9 |
| 5.3 | Consistence of fresh mortar by flow table (alternative method) | 9 |
| 5.3.1 | Method | 9 |
| 5.3.2 | Apparatus | 9 |
| 5.3.3 | Calibration | 9 |
| 5.3.4 | Procedure | 10 |
| 6 | Determination of water retention | 10 |
| 6.1 | Principle | 10 |
| 6.2 | Preparation | 10 |
| 6.3 | Apparatus | 12 |
| 6.4 | Procedure | 13 |
| 6.5 | Repeatability and reproducibility | 13 |
| 7 | Determination of air content | 14 |
| 7.1 | General | 14 |
| 7.2 | Pressure method (reference method) | 14 |
| 7.2.1 | Principle | 14 |
| 7.2.2 | Apparatus | 14 |
| 7.2.3 | Calibration | 14 |

| | | |
|--------------------|---|----|
| 7.2.4 | Procedure | 15 |
| 7.2.5 | Repeatability and reproducibility | 15 |
| 7.3 | Alcohol method (alternative method) | 16 |
| 7.3.1 | Principle | 16 |
| 7.3.2 | Apparatus | 16 |
| 7.3.3 | Procedure | 16 |
| Bibliography | | 18 |