

# DIN EN 13163:2017-02 (E)

## Thermal insulation products for buildings - Factory made expanded polystyrene (EPS) products - Specification (includes Amendment :20 16)

---

<b>Contents</b>		<b>Page</b>
European foreword .....		6
<b>1</b>	<b>Scope .....</b>	<b>9</b>
<b>2</b>	<b>Normative references .....</b>	<b>9</b>
<b>3</b>	<b>Terms, definitions, symbols, units and abbreviated terms .....</b>	<b>11</b>
<b>3.1</b>	<b>Terms and definitions .....</b>	<b>11</b>
<b>3.2</b>	<b>Symbols, units and abbreviated terms .....</b>	<b>12</b>
<b>4</b>	<b>Requirements .....</b>	<b>15</b>
<b>4.1</b>	<b>General .....</b>	<b>15</b>
<b>4.2</b>	<b>For all applications .....</b>	<b>16</b>
<b>4.2.1</b>	<b>Thermal resistance and thermal conductivity .....</b>	<b>16</b>
<b>4.2.2</b>	<b>Length and width .....</b>	<b>16</b>
<b>4.2.3</b>	<b>Thickness .....</b>	<b>16</b>
<b>4.2.4</b>	<b>Squareness .....</b>	<b>16</b>
<b>4.2.5</b>	<b>Flatness .....</b>	<b>17</b>
<b>4.2.6</b>	<b>Reaction to fire of the product as placed on the market .....</b>	<b>17</b>
<b>4.2.7</b>	<b>Durability characteristics .....</b>	<b>17</b>
<b>4.3</b>	<b>For specific applications .....</b>	<b>18</b>
<b>4.3.1</b>	<b>General .....</b>	<b>18</b>
<b>4.3.2</b>	<b>Dimensional stability .....</b>	<b>18</b>
<b>4.3.3</b>	<b>Squareness .....</b>	<b>19</b>
<b>4.3.4</b>	<b>Compressive stress at 10 % deformation .....</b>	<b>19</b>
<b>4.3.5</b>	<b>Bending strength .....</b>	<b>19</b>
<b>4.3.6</b>	<b>Tensile strength perpendicular to faces .....</b>	<b>20</b>
<b>4.3.7</b>	<b>Deformation under specified compressive load and temperature conditions .....</b>	<b>20</b>
<b>4.3.8</b>	<b>Compressive creep .....</b>	<b>21</b>
<b>4.3.9</b>	<b>Shear behaviour .....</b>	<b>21</b>
<b>4.3.10</b>	<b>Cyclic loading behaviour .....</b>	<b>22</b>
<b>4.3.11</b>	<b>Water absorption .....</b>	<b>22</b>
<b>4.3.12</b>	<b>Freeze-thaw resistance .....</b>	<b>22</b>
<b>4.3.13</b>	<b>Water vapour transmission .....</b>	<b>23</b>
<b>4.3.14</b>	<b>Dynamic stiffness .....</b>	<b>23</b>
<b>4.3.15</b>	<b>Compressibility (only applicable on EPS T products) .....</b>	<b>23</b>
<b>4.3.16</b>	<b>Apparent density .....</b>	<b>25</b>
<b>4.3.17</b>	<b>Reaction to fire of the product in standardised assemblies simulating end-use applications .....</b>	<b>25</b>
<b>4.3.18</b>	<b>Continuous glowing combustion .....</b>	<b>25</b>
<b>4.3.19</b>	<b>Release of dangerous substances .....</b>	<b>25</b>
<b>5</b>	<b>Test methods .....</b>	<b>25</b>
<b>5.1</b>	<b>Sampling .....</b>	<b>25</b>
<b>5.2</b>	<b>Conditioning .....</b>	<b>25</b>
<b>5.3</b>	<b>Testing .....</b>	<b>26</b>
<b>5.3.1</b>	<b>General .....</b>	<b>26</b>
<b>5.3.2</b>	<b>Thermal resistance and thermal conductivity .....</b>	<b>26</b>
<b>6</b>	<b>Designation code .....</b>	<b>28</b>

<b>DINEN13163:2017-02 EN 13163:2012+A2:2016 (E) 7 Assessment and Verification of the Constancy of Performance (AVCP)</b> .....	<b>30</b>
<b>7.1 General</b> .....	<b>30</b>
<b>7.2 Product Type Determination (PTD)</b> .....	<b>30</b>
<b>7.3 Factory Production Control (FPC)</b> .....	<b>30</b>
<b>8 Marking and labelling</b> .....	<b>30</b>
<b>Annex A (normative) Determination of the declared values of thermal resistance and thermal conductivity</b> .....	<b>32</b>
<b>A.1 General</b> .....	<b>32</b>
<b>A.2 Input data</b> .....	<b>32</b>
<b>A.3 Declared values</b> .....	<b>32</b>
<b>A.3.1 General</b> .....	<b>32</b>
<b>A.3.2 Case where thermal resistance and thermal conductivity are declared</b> .....	<b>32</b>
<b>A.3.3 Case where thermal resistance is declared</b> .....	<b>33</b>
<b>Annex B (normative) "Product type determination" ("PTD") and factory production control (FPC)</b> ....	<b>34</b>
<b>B.1 "Product type determination" and factory production control</b> .....	<b>34</b>
<b>B.2 Indirect testing for factory production control</b> .....	<b>39</b>
<b>B.2.1 General</b> .....	<b>39</b>
<b>B.2.2 Compressive stress at 10 % deformation</b> .....	<b>39</b>
<b>B.2.3 Thermal conductivity</b> .....	<b>40</b>
<b>B.2.4 Thickness effect</b> .....	<b>41</b>
<b>B.2.5 Dynamic stiffness</b> .....	<b>41</b>
<b>Annex C (normative) Product classification</b> .....	<b>42</b>
<b>Annex D (normative) Multi layered EPS products</b> .....	<b>44</b>
<b>D.1 General</b> .....	<b>44</b>
<b>D.2 Requirements</b> .....	<b>44</b>
<b>D.2.1 For all applications</b> .....	<b>44</b>
<b>D.2.2 For specific applications</b> .....	<b>45</b>
<b>D.3 Test methods</b> .....	<b>45</b>
<b>D.4 Evaluation of conformity</b> .....	<b>45</b>
<b>Annex E (informative) Verification of the reaction to fire classification of raw materials</b> .....	<b>46</b>
<b>E.1 General</b> .....	<b>46</b>
<b>E.2 Material covered by this annex</b> .....	<b>46</b>
<b>E.3 Preparation of samples</b> .....	<b>46</b>
<b>E.4 "Product type determination" for EPS raw material</b> .....	<b>46</b>
<b>E.5 Factory Production Control for EPS raw material</b> .....	<b>47</b>
<b>E.5.1 General</b> .....	<b>47</b>
<b>E.5.2 Testing frequency</b> .....	<b>47</b>
<b>E.6 Certification of conformity for EPS raw material</b> .....	<b>47</b>
<b>E.6.1 Bodies involved in the evaluation of conformity procedure</b> .....	<b>47</b>
<b>E.6.2 Test specimens</b> .....	<b>47</b>
<b>E.6.3 "Product type determination"</b> .....	<b>47</b>
<b>E.7 Continuous surveillance of EPS raw material</b> .....	<b>48</b>
<b>E.7.1 Production</b> .....	<b>48</b>
<b>E.7.2 Factory production control</b> .....	<b>48</b>
<b>E.8 Material certificate for EPS raw material</b> .....	<b>48</b>
<b>E.9 Requirement for raw material supply</b> .....	<b>49</b>
<b>E.9.1 Declaration for the raw material supply</b> .....	<b>49</b>
<b>E.9.2 Labelling</b> .....	<b>49</b>
<b>Annex F (informative) Additional properties</b> .....	<b>50</b>

<b>DINEN13163:2017-02 EN 13163:2012+A2:2016 (E) F.1 General</b>	<b>50</b>
<b>F.2 Long-term compressive behaviour</b>	<b>50</b>
<b>F.3 Shear behaviour</b>	<b>50</b>
<b>F.4 Water vapour diffusion resistance factor</b>	<b>51</b>
<b>F.5 Examples of determination of thermal conductivity</b>	<b>52</b>
<b>F.6 Additional information</b>	<b>53</b>
<b>Annex ZA (informative) "Clauses of this European Standard addressing the provisions of the EU Construction Products Regulation"</b>	<b>54</b>
<b>Bibliography</b>	<b>65</b>
<b>Tables Table 1 -- Classes of dimensional tolerances</b>	<b>17</b>
<b>Table 2 -- Dimensional stability under specified temperature or specified temperature and humidity conditions</b>	<b>18</b>
<b>Table 3 -- Levels for compressive stress at 10 % deformation</b>	<b>19</b>
<b>Table 4 -- Levels for bending strength</b>	<b>20</b>
<b>Table 5 -- Levels of deformation under specified compressive load and temperature conditions</b>	<b>21</b>
<b>Table 6 -- Levels for dynamic stiffness</b>	<b>23</b>
<b>Table 7 -- Classes for thickness tolerances</b>	<b>24</b>
<b>Table 8 -- Levels for compressibility</b>	<b>24</b>
<b>Table 9 -- Test methods, test specimens and conditions</b>	<b>27</b>
<b>Table A.1 -- Values for k for one sided 90 % tolerance interval with a confidence level of 90 %</b>	<b>33</b>
<b>Table B.1 -- Number of tests for "PTD" and minimum product testing frequencies</b>	<b>34</b>
<b>Table B.2 -- Minimum product testing frequencies for the reaction to fire characteristics</b>	<b>37</b>
<b>Table C.1 -- Classification of EPS products</b>	<b>42</b>
<b>Table C.2 -- Classification EPS products with acoustical properties</b>	<b>43</b>
<b>Table E.1 -- Testing frequency of raw material</b>	<b>48</b>
<b>Table F.1 -- Correlation between bending strength and shear strength</b>	<b>51</b>
<b>Table F.2 -- Tabulated values of water vapour diffusion resistance index and water vapour permeability</b>	<b>52</b>
<b>Table ZA.1 -- Relevant clauses for factory made expanded polystyrene and intended use</b>	<b>55</b>
<b>Table ZA.2 -- Systems of AVCP</b>	<b>56</b>
<b>Table ZA.3.1 -- Assignment of AVCP tasks for factory made expanded polystyrene products under system 1 for reaction to fire and system 3 (see Table ZA.2)</b>	<b>57</b>
<b>Table ZA.3.2 -- Assignment of AVCP tasks for factory made expanded polystyrene products under system 3 (see Table ZA.2)</b>	<b>58</b>
<b>Table ZA.3.3 -- Assignment of AVCP tasks for factory made expanded polystyrene products under combined system 4 for reaction to fire and system 3 (see Table ZA.2)</b>	<b>59</b>

<b>DINEN13163:2017-02 EN 13163:2012+A2:2016 (E) Figures Figure B.1 -- Relationship between compressive stress at 10 % deformation and apparent density for indirect testing .....</b>	<b>40</b>
<b>Figure F.1 -- Example of a relationship between thermal conductivity (at 50 mm reference thickness and 10 °C mean temperature) apparent density for indirect testing of non infrared absorbing EPS .....</b>	<b>53</b>
<b>Figure ZA.1 -- #Example CE marking information\$ .....</b>	<b>64</b>