

DIN EN 14351-2:2019-01 (E)

Windows and doors - Product standard, performance characteristics - Part 2: Internal pedestrian doorsets

| Contents | | Page |
|-----------------|---|-------------|
| | European foreword..... | 5 |
| 1 | Scope..... | 7 |
| 2 | Normative references..... | 8 |
| 3 | Terms, definitions and symbols..... | 10 |
| 3.1 | Terms and definitions | 10 |
| 3.2 | Symbols..... | 11 |
| 4 | Product characteristics..... | 12 |
| 4.1 | General..... | 12 |
| 4.2 | Release of dangerous substances (only for emissions into indoor air impact) (for intended use a, b and c) | 12 |
| 4.3 | Impact resistance (where relevant, only for glazed doors with injury risks) (for intended use a, b and c) | 12 |
| 4.3.1 | Glazed doors..... | 12 |
| 4.3.2 | Unframed glass doorsets | 12 |
| 4.4 | Height (for intended use a, b and c)..... | 12 |
| 4.5 | Reaction to fire..... | 12 |
| 4.5.1 | Reaction to fire of components (for intended use a, b and c)..... | 12 |
| 4.5.2 | Reaction to fire of the doorset | 13 |
| 4.6 | Direct airborne sound insulation index (only for uses where acoustic performance is required) (for intended use b) | 13 |
| 4.7 | Operating forces (only for automatic devices and only for internal landing communication doors and doors for special uses and specific requirements) (for intended use b) | 14 |
| 4.8 | Thermal transmittance (only for uses where thermal insulation performance is required) (for intended use b) | 14 |
| 4.9 | Air permeability (only for uses where air permeability performance is required for specific use with specific requirements) (for intended use b) | 14 |
| 4.10 | Ability to release (to open) (only for locked doors in escape routes) (for intended use a)..... | 14 |
| 4.11 | Durability | 14 |
| 4.11.1 | Durability of air permeability against ageing/degradation for specific use with specific requirements (for intended use b):..... | 14 |
| 4.11.2 | Durability of operating forces (safety in use) against ageing/degradation (only for automatic devices and only for internal landing communication doors and doors for special uses with specific requirements) (for intended use b) | 14 |
| 4.12 | Width | 15 |
| 4.13 | Manual operating forces..... | 15 |
| 4.14 | Mechanical strength..... | 15 |
| 4.15 | Bullet resistance | 15 |
| 4.16 | Explosion resistance | 15 |
| 4.17 | Resistance to repeated opening and closing..... | 15 |
| 4.18 | Behaviour between two different climates | 15 |
| 4.19 | Burglar resistance..... | 15 |
| 4.20 | Safety requirements for power operated pedestrian hinged doorsets..... | 16 |
| 4.21 | Ventilation | 16 |

| | | |
|---------------|---|-------------------------------------|
| 5 | Testing, assessment and sampling methods..... | 16 |
| 5.1 | General | 16 |
| 5.2 | Dangerous substances | Error! Bookmark not defined. |
| 5.3 | Impact resistance (only for glazed doors with injury risk) (for intended use a, b and c) | Error! Bookmark not defined. |
| 5.4 | Height (for intended use a, b and c)..... | 16 |
| 5.5 | Reaction to fire | 17 |
| 5.6 | Direct airborne sound insulation index (only for uses where acoustic performance is required) (for intended use b)..... | 17 |
| 5.6.1 | Reference method | 17 |
| 5.6.2 | Alternative method..... | 17 |
| 5.7 | Operating forces (only for automatic devices and only for internal landing communication doors and doors for special uses) (for intended use b)..... | 17 |
| 5.8 | Thermal transmittance (only for uses where thermal insulation performance is required) (for intended use b)..... | 17 |
| 5.8.1 | Reference method | 17 |
| 5.8.2 | Tabulation | 18 |
| 5.8.3 | Calculation | 18 |
| 5.9 | Air permeability (only for uses where air permeability performance is required for specific use with specific requirements) (for intended use b)..... | 18 |
| 5.10 | Ability to release (to open) (only for locked doors in escape routes) (for intended use a) | 18 |
| 5.11 | Durability | 18 |
| 5.11.1 | Durability of air permeability against ageing/degradation (for intended use b)..... | 18 |
| 5.11.2 | Durability of operating forces (only for automatic devices, and only for internal landing communication doors and doors for special uses with specific requirements) (for intended use b)..... | 18 |
| 5.12 | Width..... | 19 |
| 5.13 | Manual operating forces | 19 |
| 5.14 | Mechanical strength | 19 |
| 5.15 | Bullet resistance | 19 |
| 5.16 | Explosion resistance..... | 19 |
| 5.17 | Resistance to repeated opening and closing..... | 19 |
| 5.18 | Behaviour between two different climates..... | 19 |
| 5.19 | Burglar resistance..... | 19 |
| 5.20 | Safety requirements for power operated pedestrian hinged doorsets | 19 |
| 5.21 | Ventilation..... | 20 |
| 6 | Assessment and verification of constancy of performance – AVCP..... | 20 |
| 6.1 | General | 20 |
| 6.2 | Type testing | 20 |
| 6.2.1 | General | 20 |
| 6.2.2 | Test samples, testing and compliance criteria..... | 21 |
| 6.2.3 | Test reports | 21 |
| 6.2.4 | Shared other party results | 21 |
| 6.2.5 | Cascading determination of the product type results..... | 22 |
| 6.3 | Factory production control (FPC)..... | 23 |
| 6.3.1 | General | 23 |
| 6.3.2 | Requirements..... | 24 |
| 6.3.3 | Product specific requirements | 26 |
| 6.3.4 | Initial inspection of factory and of FPC..... | 26 |
| 6.3.5 | Continuous surveillance of FPC (only for products covered by AVCP system 1)..... | 27 |
| 6.3.6 | Procedure for modifications..... | 27 |

| | | |
|--|--|----|
| 6.3.7 | One-off products, pre-production products (e.g. prototypes) and products produced in very low quantity | 27 |
| 7 | Marking, Labelling and packaging | 28 |
| Annex A (informative) Product characteristics possibly affected by change of components..... | | 30 |
| A.1 | General..... | 30 |
| Annex B (normative) Tabulated values and extension of test results following size and design variations | | 32 |
| B.1 | Characteristics of internal pedestrian doorsets | 32 |
| B.2 | Sound insulation index of internal pedestrian doorsets | 34 |
| B.3 | Thermal transmittance for Internal pedestrian doorsets U_D in accordance to constructive details | 35 |
| Annex C (informative) Example of performance and requirement profile of an Internal pedestrian doorsets | | 36 |
| Annex D (informative) Examples for opening dimensions of internal pedestrian doorsets | | 37 |
| Annex E (informative) Handling, installation, maintenance and care..... | | 39 |
| Annex F (normative) Selection, preparation, mounting and fixing of test sample(s) for reaction to fire tests and field of direct application | | 40 |
| F.1 | General..... | 40 |
| F.2 | EN ISO 11925-2 (Single flame test) | 40 |
| F.2.1 | Profile..... | 40 |
| F.2.2 | Infill or door leaf..... | 42 |
| F.2.3 | Sealant between infill and profile | 42 |
| F.2.4 | Organic coating/top layers | 43 |
| F.3 | Mounting and fixing for EN 13823 (SBI-test) | 44 |
| F.3.1 | Testing of the individual components | 44 |
| F.3.2 | Testing of the doorset..... | 45 |
| F.4 | EN ISO 1182 (Non-combustibility test) | 46 |
| F.5 | EN ISO 1716 (Determination of the heat of combustion) | 46 |
| F.6 | Field of direct application | 47 |
| Annex ZA (informative) Relationship of this European Standard with Regulation (EU) N° 305/2011..... | | 48 |
| ZA.1 | Scope and relevant characteristics | 48 |
| ZA.2 | System of assessment and Verification of Constancy of Performance (AVCP) | 50 |
| ZA.3 | Assignment of AVCP tasks..... | 50 |
| Bibliography..... | | 53 |