

DIN EN 13126-8:2018-01 (E)

Building hardware - Hardware for windows and door height windows - Part 8: Requirements and test methods for Tilt and Turn, Tilt-First and Turn-Only hardware

| Contents | | Page |
|-------------------------|--|-------------|
| European foreword | | 4 |
| 1 | Scope | 7 |
| 2 | Normative references | 7 |
| 3 | Terms and definitions | 7 |
| 4 | Classification | 9 |
| 4.1 | General | 9 |
| 4.2 | Durability (1 - first box) | 9 |
| 4.3 | Mass (2 - second box) | 9 |
| 4.4 | Corrosion resistance (3 - third box) | 9 |
| 4.5 | Test sizes (4 - fourth box) | 9 |
| 4.6 | Example of classification for Tilt and Turn hardware | 10 |
| 5 | Requirements | 10 |
| 5.1 | Dangerous substances | 10 |
| 5.2 | Mechanical stability | 10 |
| 5.2.1 | Stability of the scissor stay | 10 |
| 5.2.2 | Mechanical strength of hinges | 10 |
| 5.3 | Durability | 14 |
| 5.4 | Admissible tolerances | 15 |
| 5.4.1 | Sash operation tolerance | 15 |
| 5.4.2 | Handle operation tolerance | 15 |
| 5.4.3 | Locking point variable tolerance | 15 |
| 5.5 | Resistance to additional loading | 15 |
| 5.6 | Minimum closing device resistance | 15 |
| 5.7 | Corrosion resistance | 15 |
| 5.8 | Resistance to other additional tests | 16 |
| 6 | Test equipment and preparation for the test | 16 |
| 6.1 | Test rig | 16 |
| 6.2 | Specimen | 16 |
| 6.3 | Mounting of specimen | 17 |
| 6.4 | Profile and material of specimen | 17 |
| 6.4.1 | General | 17 |
| 6.4.2 | Specimen for hardware on timber windows and door height windows | 17 |
| 6.4.3 | Specimen for hardware on PVC-U profile windows and door height windows | 17 |
| 6.4.4 | Specimen for hardware used on aluminium or steel windows and door height windows ... | 18 |
| 7 | Test procedures | 18 |
| 7.1 | Samples | 18 |
| 7.2 | Mechanical strength of hinges | 18 |
| 7.3 | General | 18 |
| 7.4 | Adjusting the sash-mass | 19 |
| 7.5 | Lubrication and adjustment of hardware | 19 |
| 7.6 | Durability test | 20 |
| 7.6.1 | Tilt cycles on hardware without positive control | 20 |
| 7.6.2 | Tilt cycles on hardware with positive control | 20 |
| 7.6.3 | Turn cycles | 21 |

| | | |
|--|--|----|
| 7.6.4 | Total cycles | 21 |
| 7.6.5 | Acceptance criteria | 21 |
| 7.6.6 | Addition loading test -- 1 000 N | 22 |
| 7.6.7 | Reveal test for hardware without turn-restrictor | 22 |
| 7.6.8 | Test for hardware with turn-restrictor | 23 |
| 7.6.9 | Rebate-hindrance test | 24 |
| 7.7 | Minimum closing device resistance test | 25 |
| 7.8 | Corrosion resistance | 25 |
| 8 | Marking | 25 |
| Annex A (informative) Typical test equipment | | 26 |
| Annex B (informative) Flowchart of the test procedures | | 27 |
| Annex C (informative) Windows types | | 28 |
| Bibliography | | 30 |