

ISO 12540:2017-03 (E)

Glass in building - Tempered soda lime silicate safety glass

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Glass products	3
5	Fracture characteristics	3
5.1	General	3
5.2	Accidental human impact	3
5.3	Fragmentation	3
6	Dimensions and tolerances	4
6.1	Nominal thickness and thickness tolerances	4
6.2	Width and length (sizes)	4
6.2.1	General	4
6.2.2	Maximum and minimum sizes	5
6.2.3	Tolerances and squareness	5
6.2.4	Edge deformation produced by vertical tempering	5
6.3	Flatness	6
6.3.1	General	6
6.3.2	Measurement of overall bow	8
6.3.3	Measurement of wave or roller wave distortion	9
6.3.4	Measurement of edge lift (for horizontally tempered safety glass only)	10
6.3.5	Measurement of perimeter deformation of glass produced by air cushion toughening process	11
6.3.6	Measurement of local distortion (for vertically tempered safety glass only)	12
6.3.7	Limitation on overall bow, roller waves and edge lift for horizontally tempered safety glass	12
6.3.8	Limitation on overall bow, wave and perimeter deformation for tempered safety glass manufactured by air cushion process	13
6.3.9	Limitation on overall bow and local distortion for vertically tempered safety glass	13
6.3.10	Other distortions	14
7	Edge work, holes, notches and cut-outs	14
7.1	General	14
7.2	Edge working of glass for tempering	14
7.3	Profiled edges	15
7.4	Round holes	15
7.4.1	General	15
7.4.2	Diameter of holes	15
7.4.3	Limitations on position of holes	15
7.4.4	Tolerances on hole diameters	17
7.4.5	Tolerances on position of holes	17
7.5	Holes/others	18
7.6	Notches and cut-outs	18
7.7	Shaped panes	19

8	Fragmentation test	19
8.1	General	19
8.2	Dimensions and number of test specimens	19
8.3	Test procedure	19
8.4	Assessment of fragmentation	20
8.5	Minimum values from the particle count	21
8.6	Selection of the longest particle	22
8.7	Maximum length of the longest particle	22
8.8	Test report	22
9	Other physical characteristics	22
9.1	Optical distortion	22
9.1.1	Tempered safety glass produced by vertical tempering	22
9.1.2	Tempered safety glass produced by horizontal tempering	22
9.2	Anisotropy (iridescence)	22
9.3	Thermal durability	23
9.4	Mechanical strength	23
9.5	Surface pre-stress	23
10	Marking	24
11	Packaging	24
	Annex A (normative) Pendulum impact test methods	25
	Annex B (informative) Alternative method for the measurement of roller wave distortion	26
	Annex C (informative) Example of particle count	28
	Annex D (informative) Method for the measurement of the surface pre-stress of tempered safety glass	31
	Bibliography	33