

ISO 20657:2017-03 (E)

Glass in building - Heat soaked tempered soda lime silicate safety glass

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Glass products	3
5	Manufacturing processes	3
5.1	General	3
5.2	Tempering process	3
5.3	Heat soak process cycles	4
5.3.1	Off-line process	4
5.3.2	In-line process	7
6	Fracture characteristics	8
6.1	General	8
6.2	Accidental human impact	8
6.3	Fragmentation	8
7	Dimensions and tolerances	9
7.1	Nominal thickness and thickness tolerances	9
7.2	Width and length (sizes)	9
7.2.1	General	9
7.2.2	Maximum and minimum sizes	10
7.2.3	Tolerances and squareness	10
7.2.4	Edge deformation produced by vertical tempering	11
7.3	Flatness	11
7.3.1	General	11
7.3.2	Measurement of overall bow	13
7.3.3	Measurement of wave or roller wave distortion	14
7.3.4	Measurement of edge lift (only for heat soaked tempered safety glass which was horizontally tempered)	15
7.3.5	Measurement of perimeter deformation of glass produced by air cushion tempering process	16
7.3.6	Measurement of local distortion (only for heat soaked tempered safety glass which was vertically tempered)	16
7.3.7	Limitation on overall bow, roller waves and edge lift for heat soaked tempered safety glass which was horizontally tempered	17
7.3.8	Limitation on overall bow, wave and perimeter deformation for heat soaked tempered safety glass manufactured by air cushion process	18
7.3.9	Limitation on overall bow and local distortion for heat soaked tempered safety glass which was vertically tempered	18
7.3.10	Other distortions	18
8	Edge work, holes, notches and cut-outs	19
8.1	General	19
8.2	Edge working of glass for tempering	19

8.3	Profiled edges	20
8.4	Round holes	20
8.4.1	General	20
8.4.2	Diameter of holes	20
8.4.3	Limitations on position of holes	20
8.4.4	Tolerances on hole diameters	21
8.4.5	Tolerances on position of holes	22
8.5	Holes/others	23
8.6	Notches and cut-outs	23
8.7	Shaped panes	23
9	Fragmentation test	23
9.1	General	23
9.2	Dimensions and number of test specimens	23
9.3	Test procedure	24
9.4	Assessment of fragmentation	24
9.5	Minimum values from the particle count	25
9.6	Selection of the longest particle	25
9.7	Maximum length of longest particle	25
9.8	Test Report	26
10	Other physical characteristics	26
10.1	Optical distortion	26
10.1.1	Heat soaked tempered safety glass produced by vertical tempering	26
10.1.2	Heat soaked tempered safety glass produced by horizontal tempering	26
10.2	Anisotropy (iridescence)	26
10.3	Thermal durability	26
10.4	Mechanical strength	27
10.5	Surface pre-stress	27
11	Marking	27
12	Packaging	28
Annex A (informative) Pendulum impact test methods		29
Annex B (informative) Alternative method for the measurement of roller wave distortion		30
Annex C (informative) Example of particle count		32
Annex D (informative) Method for the measurement of the surface pre-stress of heat soaked tempered safety glass		34
Annex E (informative) In-line heat soak process control		36
Annex F (informative) Heat soak process system calibration test		38
Bibliography		48