ISO 3008-2:2017-05 (E)

Fire-resistance tests - Part 2: Lift landing door assemblies

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Test equipment 2

5 Test conditions 2

6 Test specimen 3
6.1 Size of specimen 3
6.2 Number of specimens 3
6.3 Supporting construction 3
6.4 Installation of specimen 3

7 Conditioning 5

8 Clearances 5

9 Functionality test 5

10 Application of instrumentation 5
10.1 Temperature measurements 5
10.1.1 Furnace-temperature measurement instrument 5
10.1.2 Gas temperature measurement 5
10.1.3 Unexposed-face temperature measurement 5
10.1.4 Position of the thermocouples to determine the maximum temperature 6
10.2 Pressure measurements 7
10.2.1 Furnace pressure measurement 7
10.2.2 Gas flow pressure measurement 7
10.3 Gas flow measurement 7
10.4 CO2 concentration 7
10.4.1 Furnace 7
10.4.2 Gas flow 7
10.5 Heat-flux measurement 7
10.6 Deflection 7

11 Test procedure 7
11.1 Gap measurements 7
11.2 Functionality test 11
11.3 Flow measurement verification 12
11.4 Fire test 12

12 Performance criteria 12
12.1 Integrity (E) 12
12.2 Insulation (I) 12
12.3 Radiation (W) 12

13 Termination of test 12

14 Test report 13

15 Field of direct application of test results 13

16 Classificationprocedureanddeclarationofperformance 13
16.1 Classification periods 13
16.2 Declaration of performance 14
16.3 Classification periods 14

Annex A (normative) Description of the canopy and measuring system 15

Annex B (normative) Standard supporting construction 18

Annex C (normative)Verificationprocedureforleakageratemeasurement 19

Annex D (normative)Calculationofleakagerate 21

Annex E (informative)Extrapolationruleforttheleakagerateforhigherliftlanding door assemblies 23

Annex F (informative)Interpretingtheleakageratecurve 25

Annex G (informative)Markinginformation 26