

DIN EN 12274-5:2018-05 (E)

Slurry surfacing - Test method - Part 5: Determination of the minimum binder content and wearing resistance

Contents		Page
European foreword		3
1	Scope	4
2	Normative references	4
3	Terms and definitions	4
4	Principle	4
5	Materials	5
5.1	Coarse aggregates and fine aggregates	5
5.2	Reactive filler	5
5.3	Emulsion	5
6	Apparatus	5
6.1	Apparatus used for preparation of samples	5
6.2	Apparatus used for testing	6
7	Preparation of sample	9
7.1	Conditioning temperature	9
7.2	Water addition	10
7.3	Aggregates and reactive filler	10
7.4	Water and additive	10
7.5	Emulsion	10
7.6	Sample size	10
7.7	Curing	11
8	Test procedure	11
9	Expression of results	12
9.1	Test sample mass	12
9.2	Conversion factor	12
9.3	Test result	12
10	Test report	12
11	Precision	12
Annex A (informative) Minimum amount of emulsion for slurry surfacing with a given aggregate composition to withstand the abrasive action of traffic		13
Annex B (informative) Resistance to wear of the mix at early stage under different traffic and climatic conditions		14
B.1	General	14
B.2	Curing	14
B.3	Test procedure for determining the resistance to wear	14