

ISO 10211:2017-06 (E)

Thermal bridges in building construction - Heat flows and surface temperatures - Detailed calculations

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Symbols and subscripts	7
4.1	Symbols	7
4.2	Subscripts	7
5	Description of the method	8
5.1	Output	8
5.2	General description	8
6	Output data and input data	8
6.1	Output data	8
6.2	Calculation time intervals	9
6.3	Input data	9
7	Modelling of the construction	9
7.1	Dimension systems	9
7.2	Rules for modelling	9
7.2.1	General	9
7.2.2	Cut-off planes for a 3-D geometrical model for calculation of total heat flow and/or surface temperatures	9
7.2.3	Cut-off planes for a 2-D geometrical model	11
7.2.4	Cut-off planes in the ground	12
7.2.5	Periodic heat flows via the ground	13
7.2.6	Adjustments to dimensions	13
7.2.7	Auxiliary planes	15
7.2.8	Quasi-homogeneous layers and materials	15
7.3	Conditions for simplifying the geometrical model	15
7.3.1	General	15
7.3.2	Conditions for adjusting dimensions to simplify the geometrical model	16
7.3.3	Conditions for using quasi-homogeneous material layers to simplify the geometrical model	17
8	Input data specifications	20
8.1	General	20
8.2	Thermal conductivities of materials	21
8.3	Surface resistances	21
8.4	Boundary temperatures	21
8.5	Thermal conductivity of quasi-homogeneous layers	21
8.6	Equivalent thermal conductivity of air cavities	21
8.7	Determining the temperature in an adjacent unheated room	22
9	Calculation method	22

9.1	Solution technique	22
9.2	Calculation rules	22
9.2.1	Heat flows between material cells and adjacent environment	22
9.2.2	Heat flows at cut-off planes	22
9.2.3	Solution of the formulae	22
9.2.4	Calculation of the temperature distribution	23
10	Determination of thermal coupling coefficients and heat flow rate from 3-D calculations	
	10.1 Two boundary temperatures, unpartitioned model	23
10.2	Two boundary temperatures, partitioned model	23
10.3	More than two boundary temperatures	24
11	Calculations using linear and point thermal transmittances from 3-D calculations	25
11.1	Calculation of thermal coupling coefficient	25
11.2	Calculation of linear and point thermal transmittances	25
12	Determination of thermal coupling coefficient, heat flow rate and linear thermal transmittance from 2-D calculations	26
12.1	Two boundary temperatures	26
12.2	More than two boundary temperatures	26
12.3	Determination of the linear thermal transmittance	27
12.4	Determination of the linear thermal transmittance for wall/floor junctions	27
12.4.1	All cases	27
12.4.2	Option A	27
12.4.3	Option B	29
12.5	Determination of the external periodic heat transfer coefficient for ground floors	31
13	Determination of the temperature at the internal surface	32
13.1	Determination of the temperature at the internal surface from 3-D calculations	32
13.1.1	Two boundary temperatures	32
13.1.2	More than two boundary temperatures	32
13.2	Determination of the temperature at the internal surface from 2-D calculations	33
13.2.1	Two boundary temperatures	33
13.2.2	Three boundary temperatures	33
14	Report	33
14.1	Input data	33
14.2	Output data	34
14.2.1	General	34
14.2.2	Calculation of the heat transmission using the thermal coupling coefficient	34
14.2.3	Calculation of the surface temperatures using weighting factors	34
14.2.4	Additional output data	34
14.2.5	Estimate of error	35
Annex A (normative)	Input and method selection data sheet -- Template	36
Annex B (informative)	Input and method selection data sheet -- Default choices	38
Annex C (normative)	Validation of calculation methods	40
Annex D (normative)	Examples of the determination of the linear and point thermal transmittances	47
Annex E (normative)	Determination of values of thermal coupling coefficient and temperature weighting factor for more than two boundary temperatures	50
Bibliography	55