ISO 12354-1:2017-07 (E)

Building acoustics - Estimation of acoustic performance of buildings from the performance of elements - Part 1: Airborne sound ins ulation between rooms

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 2
3.1 Quantities to express building performance 2
3.2 Quantities to express element performance 3
3.3 Other terms and quantities 6

4 Calculation models 7
4.1 General principles 7
4.2 Detailed model for structure-borne transmission 10
4.2.1 Input data 10
4.2.2 Transfer of input data to in situ values 11
4.2.3 Determination of direct and flanking transmission in situ 13
4.2.4 Limitations 14
4.3 Detailed model for airborne transmission 15
4.3.1 Determination from measured airborne direct transmission for small technical elements 15
4.3.2 Determination from measured total indirect transmission 15
4.3.3 Determination from the performance of the separate elements of a system 15
4.4 Simplified model 15
4.4.1 General 15
4.4.2 Calculation procedure 15
4.4.3 Input data 18
4.4.4 Limitations 19

5 Accuracy 19

Annex A (normative) Symbols 20

Annex B (informative) Sound reduction index 25

Annex C (informative) Structural reverberation time: Type A elements 34

Annex D (informative) Sound reduction index improvement of additional layers 37

Annex E (informative) Vibration transmission over junctions: case of heavy buildings 42

Annex F (informative) Vibration transmission over junctions: case of lightweight buildings 51

Annex G (informative)Determinationofnormalizedflankingleveldifference 59

Annex H (informative) Determination of indirect airborne transmission from performance of system elements 62

Annex I (informative) Sound insulation in the low frequency range 64

Annex J (informative) Guidelines for practical use 66

Annex K (informative) Estimation of uncertainty 74

Annex L (informative) Calculation examples 77

Bibliography 92