

ISO 12354-1:2017-07 (E)

Building acoustics - Estimation of acoustic performance of buildings from the performance of elements - Part 1: Airborne sound insulation between rooms

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
3.1	Quantities to express building performance	2
3.2	Quantities to express element performance	3
3.3	Other terms and quantities	6
4	Calculation models	7
4.1	General principles	7
4.2	Detailed model for structure-borne transmission	10
4.2.1	Input data	10
4.2.2	Transfer of input data to in situ values	11
4.2.3	Determination of direct and flanking transmission in situ	13
4.2.4	Limitations	14
4.3	Detailed model for airborne transmission	15
4.3.1	Determination from measured airborne direct transmission for small technical elements	15
4.3.2	Determination from measured total indirect transmission	15
4.3.3	Determination from the performance of the separate elements of a system	15
4.4	Simplified model	15
4.4.1	General	15
4.4.2	Calculation procedure	15
4.4.3	Input data	18
4.4.4	Limitations	19
5	Accuracy	19
Annex A (normative)	Symbols	20
Annex B (informative)	Sound reduction index	25
Annex C (informative)	Structural reverberation time: Type A elements	34
Annex D (informative)	Sound reduction index improvement of additional layers	37
Annex E (informative)	Vibration transmission over junctions: case of heavy buildings	42
Annex F (informative)	Vibration transmission over junctions: case of lightweight buildings	51
Annex G (informative)	Determination of normalized flanking level difference	59
Annex H (informative)	Determination of indirect airborne transmission from performance of system elements	62
Annex I (informative)	Sound insulation in the low frequency range	64

Annex J (informative) Guidelines for practical use	66
Annex K (informative) Estimation of uncertainty	74
Annex L (informative) Calculation examples	77
Bibliography	92