

DIN EN 1279-1:2018-10 (E)

Glass in Building - Insulating glass units - Part 1: Generalities, system description, rules for substitution, tolerances and visual quality

| Contents | | Page |
|---|---|-------------|
| European foreword | | 4 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 7 |
| 4 | Symbols and abbreviations for edge seal | 14 |
| 5 | Requirements | 15 |
| 5.1 | General | 15 |
| 5.2 | Glass panes/components | 16 |
| 5.2.1 | General | 16 |
| 5.2.2 | Basic glasses | 16 |
| 5.2.3 | Special basic glasses | 16 |
| 5.2.4 | Strengthened glasses | 16 |
| 5.2.5 | Thermally toughened safety glasses | 17 |
| 5.2.6 | Laminated glasses | 17 |
| 5.2.7 | Coated glasses | 17 |
| 5.2.8 | Surface worked glass | 17 |
| 5.2.9 | Curved glass | 17 |
| 5.3 | Cavity fillings | 18 |
| 5.4 | Cavity inserts | 18 |
| 5.5 | Shapes | 18 |
| 6 | Requirements | 18 |
| 6.1 | Durability of insulating glass units | 18 |
| Annex A (normative) System description of insulating glass units | | 22 |
| Annex B (normative) Examples of insulating glass unit systems | | 23 |
| B.1 | General | 23 |
| B.2 | Organic sealed insulating glass units with rigid hollow spacer | 23 |
| B.3 | Insulating glass units sealed by hot applied flexible spacer incorporating desiccant | 23 |
| B.4 | Insulating glass units with prefabricated flexible spacer | 24 |
| B.5 | Organic sealed insulating glass units with U-channel shaped spacer incorporating desiccant matrix | 25 |
| B.6 | Air filled insulating glass units sealed by a metal strip between the glass panes | 27 |
| Annex C (informative) Compatibility of components within an insulating glass unit system | | 28 |
| C.1 | Compatibility | 28 |
| C.2 | Diffusion and equilibrium | 28 |
| C.3 | Contact | 28 |
| C.4 | Interaction | 28 |
| C.5 | Factors affecting compatibility | 28 |
| Annex D (normative) Rules to substitute materials and components, possible changes within components and addition in the system description | | 30 |

| | | |
|---|---|----|
| D.1 | General comments | 30 |
| D.2 | Tables of possibilities to substitute materials and components, and of possible changes within components | 30 |
| D.3 | Addition of components | 35 |
| D.3.1 | Addition of cavity inserts without change of the permeation barrier design | 35 |
| D.3.2 | Addition of cavity inserts with change of the permeation barrier design | 35 |
| Annex E (informative) Edge seal strength comparison in case of substituting outer sealant | | 36 |
| Annex F (normative) Visual quality of insulating glass units | | 37 |
| F.1 | General | 37 |
| F.2 | Observation conditions | 37 |
| F.3 | Insulating glass unit made of two panes of monolithic glass | 38 |
| F.3.1 | Spot faults | 38 |
| F.3.2 | Residues | 39 |
| F.3.3 | Linear / extended fault | 39 |
| F.4 | Insulating glass units other than made of two monolithic glass panes | 39 |
| F.5 | Insulating glass unit containing a heat treated glass | 40 |
| F.6 | Edge defects | 40 |
| F.7 | Tolerance on spacer straightness | 40 |
| F.8 | Curved insulating glass units | 41 |
| Annex G (informative) Other visual aspects of insulating glass units | | 42 |
| G.1 | General | 42 |
| G.2 | Inherent colour | 42 |
| G.3 | Difference in insulating glass unit colour | 42 |
| G.4 | Interference effect | 42 |
| G.5 | Specific effect due to barometric conditions | 42 |
| G.6 | Multiple reflections | 42 |
| G.7 | Anisotropy (iridescence) | 43 |
| G.8 | Condensation on the external surface of the insulating glass unit | 43 |
| G.9 | Wetting of glass surfaces | 43 |
| Bibliography | | 44 |