

# DIN EN 1279-2:2018-10 (E)

## Glass in building - Insulating glass units - Part 2: Long term test method and requirements for moisture penetration

---

<b>Contents</b>		<b>Page</b>
European foreword .....		3
<b>1</b>	<b>Scope .....</b>	<b>5</b>
<b>2</b>	<b>Normative references .....</b>	<b>5</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>5</b>
<b>4</b>	<b>Symbols and abbreviations .....</b>	<b>5</b>
<b>5</b>	<b>Requirements .....</b>	<b>6</b>
<b>6</b>	<b>Method of long-term test .....</b>	<b>6</b>
<b>6.1</b>	<b>Principle .....</b>	<b>6</b>
<b>6.2</b>	<b>Number, description and selection of test specimens .....</b>	<b>6</b>
<b>6.3</b>	<b>Climate conditions in cabinet .....</b>	<b>7</b>
<b>6.4</b>	<b>Procedure .....</b>	<b>9</b>
<b>6.5</b>	<b>Calculation of moisture penetration index I .....</b>	<b>9</b>
<b>6.6</b>	<b>Precision of test method .....</b>	<b>10</b>
<b>7</b>	<b>Determination of moisture content .....</b>	<b>10</b>
<b>7.1</b>	<b>Methods available .....</b>	<b>10</b>
<b>7.2</b>	<b>Sampling method .....</b>	<b>11</b>
<b>7.2.1</b>	<b>Sampling of desiccant in bulk .....</b>	<b>11</b>
<b>7.2.2</b>	<b>Sampling of preformed flexible spacer incorporating desiccant .....</b>	<b>11</b>
<b>8</b>	<b>Test report .....</b>	<b>14</b>
<b>Annex A (normative) Moisture content in insulating glass units without desiccant .....</b>		<b>16</b>