DIN EN 13126-6:2018-10 (E)

Building hardware - Hardware for windows and door height windows - Requirements and test methods - P art 6: Variable geometry stay hinges (with or without a friction stay)

Contents

Page

European foreword ... 4

1 Scope ... 6

2 Normative references ... 6

3 Terms and definitions ... 6

4 Classification ... 7
4.1 General ... 7
4.2 Durability (1 – first box) ... 8
4.3 Mass (2 – second box) ... 8
4.4 Corrosion resistance (3 – third box) ... 8
4.5 Test sizes (4 – fourth box) ... 8
4.6 Application (5 – fifth box) ... 10
4.7 Example of classification for variable/parallel geometry stay hinges ... 10

5 Requirements ... 10
5.1 Dangerous substances ... 10
5.2 Integrated restrictors ... 11
5.3 Durability ... 11
5.4 Pull-in and pull-in abuse test ... 11
5.5 Parallelism test ... 11
5.6 Friction test (where applicable) ... 11
5.7 Obstructed track test ... 12
5.8 Ease of sash movement test ... 12
5.9 Durability test ... 12
5.10 Simulated negative pressure test ... 13
5.11 Static load test ... 13
5.12 Additional load test ... 14
5.13 Corrosion resistance ... 14

6 Test equipment and preparation for the test ... 14
6.1 Test-rig ... 14
6.2 Specimen ... 14
6.3 Mounting of specimen ... 15
6.4 Additional equipment ... 15
6.4.1 Block for pull-in abuse test ... 15
6.4.2 Steel cross for simulated negative pressure test ... 15

7 Test procedures ... 15
7.1 Samples ... 15
7.2 General ... 15
7.3 Adjusting the sash-mass ... 16
7.4 Lubrication and adjustment of hardware ... 16
7.5 Pull-in test ... 16
7.5.1 General ... 16
7.5.2 Pull-in test procedure ... 16
7.5.3 Acceptance criteria ... 16
7.6 Friction test ... 17
7.6.1 General ... 17

7.6.2 Friction test procedure **17**
7.6.3 Acceptance criteria **17**
7.7 Obstructed track test **17**
7.7.1 Procedure – side hung and top hung windows **17**
7.7.2 Procedure – parallel opening windows **18**
7.7.3 Acceptance criteria **18**
7.8 Pull-in abuse test **18**
7.8.1 General **18**
7.8.2 Procedure – pull-in abuse test **18**
7.8.3 Acceptance criteria **19**
7.9 Ease of sash movement test **19**
7.9.1 Procedure – side and top hung opening windows **19**
7.9.2 Procedure – parallel opening windows **19**
7.9.3 Acceptance criteria **19**
7.10 Durability test **20**
7.10.1 Procedure – top hung and side hung windows **20**
7.10.2 Procedure – parallel opening windows **20**
7.10.3 Cycles **20**
7.10.4 Egress easy clean side hung windows **20**
7.10.5 Acceptance criteria **20**
7.11 Simulated negative pressure test (excluding parallel windows) **21**
7.11.1 Procedure **21**
7.11.2 Acceptance criteria **21**
7.12 Static load test procedure **21**
7.12.1 Procedure **21**
7.12.2 Acceptance criteria **22**
7.13 Additional load test **22**
7.13.1 Procedure **22**
7.13.2 Acceptance criteria **22**
7.14 Parallelism test **22**
7.14.1 Procedure – closed position **22**
7.14.2 Procedure – open position **22**
7.14.3 Acceptance criteria **22**
7.15 Corrosion resistance **23**
8 Marking **23**
Annex A (informative) **Types of variable/parallel geometry stay hinges** **24**
Annex B (informative) **Test method diagrams** **26**
Annex C (informative) **Flow chart of test procedures** **34**
Annex D (informative) **Window types** **36**
Bibliography **40**