

ISO 1716:2018 (E)

Reaction to fire tests for products — Determination of the gross heat of combustion (calorific value)

Contents

	Foreword
1	Scope
2	Normative references
3	Terms and definitions
4	Principle
5	Test apparatus
6	Reagents and materials
7	Test specimens
7.1	General
7.2	Sampling
7.2.1	General
7.2.2	Loose-fill material
7.2.3	Liquid-applied products
7.2.4	Thin film products
7.3	Determination of surface density
7.4	Grinding
7.5	Type of specimen
7.6	Conditioning
7.7	Number of test specimens
7.8	Determination of mass
7.9	Crucible method
7.10	“Cigarette” method
8	Test procedure
8.1	General
8.2	Calibration procedure
8.2.1	Determination of the water equivalent
8.2.2	Conditions for recalibration
8.3	Standard test procedure
9	Expression of results
9.1	Corrections for manual apparatus
9.2	Corrections for isothermal calorimeter (see Annex C)
9.3	Calculation of the gross heat of combustion of the specimen
9.4	Calculation of the gross heat of combustion of the product
9.4.1	General
9.4.2	Homogeneous product
9.4.3	Non-homogeneous product
10	Test report
11	Validity of test results
Annex A	(normative) Calculation of net heat of combustion
Annex B	(informative) Precision of test method

- B.1 CEN/TC 127 round-robin exercise
- B.2 EGOLF round-robin exercise, 2008-2009
- Annex C (informative) Calculation by graph of the corrective term, c , necessary because of the cooling of the calorimeter
- Annex D (informative) Example of determination of the gross heat of combustion of a non-homogeneous product
 - D.1 Non-homogeneous product to be tested
 - D.2 Sampling of the non-homogeneous product
 - D.2.1 Delamination of the product
 - D.2.2 Determination of the area weight of each component
 - D.3 Determination of the gross heat of combustion of each component
 - D.4 Sampling when substantial and non-substantial components as well as several internal and external components are placed over each other
 - D.4.1 Non homogeneous product to be tested
 - D.4.2 Sampling of the Non-homogeneous product

Page count: 30