

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols
5	Materials
5.1	Steel
5.1.1	High strength steel grades
5.1.2	Cold temperature operation
5.2	Aluminium alloys
6	Nominal operating loads
7	General operating loads
7.1	Permanent loads
7.2	Vertical imposed loads due to holding devices
7.2.1	Holding device engagement load
7.2.2	Holding devices securing load
7.3	Lateral imposed loads
7.3.1	Fixed guide systems in vertical shafts
7.3.2	Rope guide systems
7.3.3	Decline shaft conveyance wheel loads
7.4	Winder system loads
7.4.1	Acceleration/deceleration load
7.4.2	Trip-out load
7.4.3	Tail-rope load
7.4.4	Vertical friction load
7.5	Roof loads
8	Personnel winding loads
8.1	Standing personnel load
8.2	Seated personnel load
8.3	Loading of cages
8.4	Loading of cages in decline shafts
8.5	Dogging system load
9	Material and equipment winding loads
9.1	Floor loads
9.1.1	Static load
9.1.2	Impact loads
9.1.2.1	Rolling stock load
9.1.2.2	Rubber-tyred, self-propelled vehicle load
9.1.2.3	Crawler-mounted, self-propelled vehicle load
9.1.2.4	Other material and equipment loads
9.2	Underslung loads or trailing loads
10	Rock winding loads

- 10.1 Skip loads
 - 10.1.1 General
 - 10.1.2 Static rock loads
 - 10.1.3 Bridle and top transom loads during filling
 - 10.1.4 Reference rock pressure
 - 10.1.5 Pressure during filling or travelling in the shaft
 - 10.1.5.1 Pressure on skip bottom (p1)
 - 10.1.5.2 Side pressure (p2)
 - 10.1.6 Pressures during emptying
 - 10.1.7 Load on tipping rollers
 - 10.1.8 Skip return-stop loads
- 10.2 Kibble loads
 - 10.2.1 Static rock or slurry loads
 - 10.2.2 Reference rock or slurry pressure
 - 10.2.3 Pressure during filling
 - 10.2.3.1 Pressure on kibble bottom (p1)
 - 10.2.3.2 Side pressure (p2)
 - 10.2.4 Pressures during emptying
 - 10.2.5 Heavy kibble payloads
- 11 Emergency loads
 - 11.1 Rope emergency load
 - 11.1.1 Permanent operating conveyances with fixed rope winders
 - 11.1.2 Permanent operating conveyances with friction winders
 - 11.1.3 Temporary equipping, maintenance and inspection conveyances
 - 11.1.4 Slung equipment and conveyances
 - 11.1.5 Kibbles and kibble cross-heads
 - 11.2 Emergency drop-back loads
 - 11.2.1 General
 - 11.2.2 All permanent conveyances
 - 11.2.3 Kibbles and kibble cross-heads
 - 11.3 Roof impact loads
 - 11.4 Skip loads
 - 11.4.1 General
 - 11.4.2 Reference rock pressure
 - 11.4.3 Pressure during filling or travelling in the shaft
 - 11.4.3.1 Pressure on skip bottom (p1)
 - 11.4.3.2 Side pressure (p2)
 - 11.4.3.3 Single rock impact (R_i , R_k) during filling
 - 11.5 Emergency stopping device loads
 - 11.5.1 Overspeed device
 - 11.6 Application of emergency loads
- 12 Design procedures
 - 12.1 Design loads
 - 12.2 Design codes
 - 12.3 Design for emergency loads
 - 12.3.1 Steel components
 - 12.3.2 Aluminium components
 - 12.3.3 Special considerations
 - 12.3.3.1 Conveyance roofs
 - 12.4 Fatigue
- 13 Construction requirements
 - 13.1 General
 - 13.2 Confirmation of design by testing
 - 13.2.1 Testing of operating mechanisms
 - 13.3 Construction tolerances
- Annex A (informative) Load factors and load combinations
 - A.1 General
 - A.2 Operating conditions
 - A.2.1 Partial load factors
 - A.2.2 Load combinations

- A.2.3** **Fatigue design loads**
- A.3** **Emergency conditions**
- A.4** **Conveyance installation**

Annex B (informative) Examples of tipping roller and skip return-stop loads

- B.1** **Tipping roller load**
- B.1.1** **Vertical shafts**
- B.1.2** **Decline shafts**
- B.2** **Skip return stop loads — Vertical shafts and decline shafts**

Page count: 29