

# ISO 17749:2018 (E)

## Thermal insulation products — Sheep wool mat and board — Specification

---

### Contents

|         |   |
|---------|---|
|         | Foreword  |
| 1       | Scope   |
| 2       | Normative references  |
| 3       | Terms and definitions   |
| 4       | Symbols and abbreviated terms   |
| 4.1     | Symbols   |
| 4.2     | Abbreviated terms   |
| 5       | Requirements  |
| 5.1     | General   |
| 5.2     | Material properties   |
| 5.2.1   | Thermal resistance and thermal conductivity   |
| 5.2.2   | Length and width  |
| 5.2.3   | Thickness   |
| 5.2.4   | Reaction to fire  |
| 5.2.5   | Moisture content  |
| 5.3     | Specific requirements   |
| 5.3.1   | Apparent density  |
| 5.3.2   | Sound absorption  |
| 5.3.3   | Formaldehyde release  |
| 5.3.4   | Thickness recovery ratio  |
| 6       | Test methods  |
| 6.1     | Sampling  |
| 6.2     | Conditioning  |
| 6.3     | Procedure   |
| 6.3.1   | General   |
| 6.3.2   | Thermal resistance and thermal conductivity   |
| 7       | Designation code  |
| 8       | Product conformity  |
| 8.1     | General   |
| 8.2     | Initial type testing  |
| 8.3     | Factory production control  |
| 9       | Marking and labelling   |
| Annex A | (normative) Determination of the declared values of thermal resistance and thermal conductivity |
| A.1     | General   |
| A.2     | Input data  |
| A.3     | Declared values   |
| A.3.1   | Case where both thermal resistance and thermal conductivity are declared                        |
| A.3.2   | Case where only thermal resistance is declared  |
| Annex B | (normative) Factory production control  |
| Annex C | (normative) Determination of the thermal conductivity in relation to moisture content           |

**Annex D (normative) Thickness-recovery ratio test method**

- D.1 General**
- D.2 Test procedure**
- D.3 Calculation**
- D.4 Report**

**Annex E (informative) Evaluation of conformity**

**Page count: 17**