

# ISO 18407:2018 (E)

## Simplified design of prestressed concrete tanks for potable water

---

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols
5	Design principles
6	Load
6.1	General
6.2	Deadweight
6.3	Imposed load
6.4	Hydrostatic water pressure
6.5	Prestress
6.5.1	General
6.5.2	Prestressing force immediately after prestressing
6.5.3	Effective prestressing force
6.5.4	Indeterminate forces due to prestress
6.6	Creep and drying shrinkage of concrete
6.7	Effect of temperature
6.8	Seismic action
6.9	Wind load
6.10	Snow load
6.11	Earth pressure
6.12	Uplift pressure force
6.13	Other loads
7	Structural analysis
7.1	Calculation of member force
7.2	Concrete
7.2.1	Strength
7.2.2	Modulus of elasticity
7.2.3	Poisson's ratio
7.2.4	Drying shrinkage
7.2.5	Creep
7.3	Steel
7.3.1	Strength
7.3.2	Modulus of elasticity
7.3.3	Relaxation
7.4	Calculation of tensile reinforcement
8	Stress limit
8.1	General
8.2	Stress limit of reinforced concrete members
8.2.1	Stress limit of concrete
8.2.2	Stress limit of reinforcement
8.3	Stress limit of prestressed concrete members
8.3.1	Stress limit of concrete

- 8.3.2 Tensile stress limit of prestressing steel
- 8.3.3 Stress limit of reinforcement
- 8.3.4 Augmentation of tensile stress limit of concrete
- 9 Verification of safety against earthquake
  - 9.1 Principles of seismic design
    - 9.1.1 General
    - 9.1.2 Ground motion levels
    - 9.1.3 Levels of earthquake resistance
    - 9.1.4 Effects of earthquake
    - 9.1.5 Seismic design procedure
  - 9.2 Input earthquake motion
    - 9.2.1 Seismic design method
    - 9.2.2 Design seismic coefficients for the seismic coefficient method for Level 1 ground motion
    - 9.2.3 Design seismic coefficients for the seismic coefficient method for Level 2 ground motion
    - 9.2.4 Seismic input for design by dynamic analysis
  - 9.3 Verification of structural safety
    - 9.3.1 Effects of earthquake
      - 9.3.1.1 General
      - 9.3.1.2 Inertia force derived from deadweight, etc
      - 9.3.1.3 Dynamic water pressure during an earthquake
    - 9.3.2 Combination of loads
    - 9.3.3 Calculation of member forces
    - 9.3.4 Safety verification
  - 9.4 Investigation for foundation
- 10 General structural details
  - 10.1 Prestressing steel
    - 10.1.1 Clear distance
    - 10.1.2 Concrete cover
    - 10.1.3 Arrangement of curved prestressing steel
    - 10.1.4 Arrangement of anchorages and couplers
    - 10.1.5 Protection of anchorage zone
    - 10.1.6 Reinforcement of concrete near anchorages
  - 10.2 Steel reinforcement
    - 10.2.1 Clear distance
    - 10.2.2 Concrete cover
    - 10.2.3 Bend configurations of reinforcement
    - 10.2.4 Splices in reinforcement
    - 10.2.5 Anchoring of reinforcement
    - 10.2.6 Welded wire fabric
  - 10.3 Concrete joints
    - 10.3.1 Construction joints
    - 10.3.2 Joints between precast concrete members
  - 10.4 Reinforcement for opening
- 11 Design of members
  - 11.1 Method of calculating member force
    - 11.1.1 Analysis method
    - 11.1.2 Analysis model
  - 11.2 Component division
  - 11.3 Roof
    - 11.3.1 Structural types
      - 11.3.2 Design in general
        - 11.3.2.1 Loads for roof design
        - 11.3.2.2 Design of a spherical dome
          - 11.3.2.3 Design of the dome ring
          - 11.3.2.4 Design of slab roof
    - 11.4 Tank wall
      - 11.4.1 Structural types
        - 11.4.2 Design in general
          - 11.4.2.1 Loads for tank wall

- 11.4.2.2 Combinations of loads
- 11.4.2.3 Design of the tank wall
- 11.4.2.4 Method of applying prestress
- 11.4.2.5 Pilasters
- 11.4.2.6 Design of the tank wall bottom
- 11.5 Base slab
- 11.5.1 Structural types
- 11.5.2 Design in general
- 11.5.2.1 Loads for base slab
- 11.5.2.2 Load combinations
- 11.5.2.3 General design of base slab
- 11.5.2.4 One-layer base slab structure
- 11.5.2.5 Two-layer base slab structure

## 12 Materials

- 12.1 Quality of materials
- 12.1.1 General
- 12.1.2 Concrete materials
- 12.1.2.1 Cement
- 12.1.2.2 Water
- 12.1.2.3 Fine aggregate
- 12.1.2.4 Coarse aggregate
- 12.1.2.5 Admixtures
- 12.1.3 Concrete
- 12.1.3.1 General
- 12.1.3.2 Strength
- 12.1.4 Prestressing steel
- 12.1.5 Steel reinforcement
- 12.1.6 Welded wire fabric
- 12.1.7 Anchorages and couplers
- 12.1.8 Sheath
- 12.1.9 Coating materials for protecting prestressing steel
- 12.1.9.1 Grout for prestressed concrete
- 12.1.9.2 Coating materials for unbonded prestressing steel

## 13 Tank appurtenances

- 13.1 Ladders/stairs and handrails
- 13.2 Manhole and water pilot hole
- 13.3 Ventilators
- 13.4 Lightning rods
- 13.5 Piping
- 13.6 Catch basin
- 13.7 Water-level gauge
- 13.8 Rainwater treatment
- 13.9 Protection equipment

### Annex A (informative) Reference design flow

### Annex B (informative) Design seismic coefficients for the seismic coefficient method

- B.1 Level 1 ground motion
- B.2 Level 2 ground motion

### Annex C (informative) Seismic input for design by dynamic analysis

### Annex D (informative) Example of material specifications

- D.1 Concrete
- D.1.1 Modulus of elasticity
- D.1.2 Drying shrinkage
- D.1.3 Creep
- D.2 Steel
- D.2.1 Modulus of elasticity
- D.2.2 Relaxation
- D.3 Stress limit
- D.3.1 Stress limit of reinforced concrete members

- D.3.1.1 Stress limit of concrete
- D.3.1.2 Stress limit of reinforcement
- D.3.2 Stress limit of prestressed concrete members
  - D.3.2.1 Stress limit of concrete
  - D.3.2.2 Tensile stress limit of prestressing steel
  - D.3.2.3 Stress limit of reinforcement
  - D.3.2.4 Augmentation of tensile stress limit of concrete

#### Annex E (informative) Example of design calculation

- E.1 Outline
  - E.1.1 Outline of design
  - E.1.2 Outline of the structure
- E.2 Design conditions
  - E.2.1 Basic dimensions and general shape
  - E.2.2 Construction site and ground conditions
  - E.2.3 Design loads
    - E.2.3.1 Classifications of design loads
    - E.2.3.2 Load type and load intensity
  - E.2.4 Materials properties
    - E.2.4.1 Concrete
    - E.2.4.2 Prestressing steel
    - E.2.4.3 Reinforcing bars
    - E.2.4.4 Stress loss of prestressing steel
  - E.2.5 Stress limit
  - E.2.6 Material strength
  - E.2.7 Material factor
  - E.2.8 Minimum reinforcement and minimum cover depth
- E.3 Design of the dome roof
  - E.3.1 Design conditions
  - E.3.2 Cross-section force acting on the dome
    - E.3.2.1 Calculation of the dome load
    - E.3.2.2 Stress generated in the dome
  - E.3.3 Steel reinforcement arrangement of the dome
- E.4 Design of the dome ring
  - E.4.1 Design conditions
  - E.4.2 Calculation of horizontal thrust
    - E.4.2.1 Loads on the dome
    - E.4.2.2 Dome horizontal thrust
  - E.4.3 Design of prestressing force
    - E.4.3.1 Centre positions of prestressing steel
    - E.4.3.2 Section size of pilaster
    - E.4.3.3 Required prestressing force
    - E.4.3.4 Calculation of the effective tensile force of prestressing steel
    - E.4.3.5 Prestressing steel arrangement in the circumferential direction
- E.5 Design of wall
  - E.5.1 Design conditions
  - E.5.2 Calculation of cross-section force
    - E.5.2.1 Basic formula and solution
    - E.5.2.2 M<sub>0</sub> and Q<sub>0</sub> at the wall bottom
    - E.5.2.3 Bending moment, shearing force and circumferential axial force at an arbitrary point
    - E.5.2.4 Stress due to deadweight
    - E.5.2.5 Stress due to imposed load
    - E.5.2.6 Cross-section force incorporating the effects of the haunch at wall bottom and elastic fixation
  - E.5.3 Design of circumferential prestressing force
    - E.5.3.1 Centre positions of prestressing steel
    - E.5.3.2 Section size of pilaster
    - E.5.3.3 Calculation of the effective tensile force of prestressing steel
    - E.5.3.4 Required prestressing force
    - E.5.3.5 Arrangement of circumferential prestressing steel
  - E.5.4 Design of vertical prestressing force
    - E.5.4.1 Calculation of effective prestressing force
    - E.5.4.2 Axial force and eccentric moment due to vertical prestressing steel
    - E.5.4.3 Cross-section force and stress at wall bottom for selecting vertical prestressing steel

E.5.4.4	Required prestressing force
E.5.4.5	Number of vertical prestressing steel required
E.5.4.6	Stress due to vertical prestressing force
E.5.5	Cross-section force and stress of the tank wall
E.5.6	Combined stress
E.5.7	Verification regarding shear
E.5.7.1	General
E.5.7.2	Shear stress
E.5.7.3	Diagonal tensile stress
E.5.8	Verification of safety against an earthquake
E.5.8.1	Calculation of cross-section force
E.5.8.2	Verification with respect to Level 1 ground motion
E.5.8.3	Verification with respect to Level 2 ground motion
E.5.8.4	Verification of sloshing height
E.6	Design of base slab
E.6.1	Design of base slab
E.6.2	Ring plate length
E.6.3	Calculation of cross-section force
E.6.3.1	Design load
E.6.3.2	Modelling
E.6.3.3	Calculation of cross-section force
E.6.4	Bar arrangement of base slab
E.6.4.1	Minimum reinforcement content
E.6.4.2	Calculation of reinforcement content
E.6.4.3	Calculation of reinforcement content
E.6.5	Verification of safety against an earthquake
E.6.5.1	Verification with respect to Level 1 ground motion
E.6.5.2	Verification with respect to Level 2 ground motion
E.7	Stability calculation
E.7.1	Horizontal force and overturning moment
E.7.1.1	Deadweight
E.7.1.2	Overturning moment due to dynamic water pressure
E.7.2	Verification of bearing capacity
E.7.3	Verification regarding sliding
E.7.4	Verification regarding overturning

Page count: 174