

DIN EN 12697-31:2020-04 (E)

Bituminous mixtures - Test methods - Part 31: Specimen preparation by gyratory compactor

Contents		Page
European foreword		4
1	Scope	6
2	Normative references	6
3	Terms, definitions and symbols	6
3.1	Terms and definitions	6
3.2	Symbols	7
4	Principle	9
5	Apparatus	9
5.1	Test device	9
5.2	Metallic moulds	10
5.3	Round metallic inserts	10
5.4	Device for measuring the distance between inserts	10
5.5	Device for counting the number of rotations with a precision of one revolution	10
5.6	Other usual equipments	10
6	Preparation of specimens	11
6.1	Mass of mixture to be introduced in the mould	11
6.1.1	Preparation of specimens for further mechanical testing	11
6.1.2	Preparation of specimens for void content requirement	11
6.2	Preparation of mixtures	12
7	Test procedure	13
7.1	Preliminary setting	13
7.1.1	Pre-load stress	13
7.1.2	Stress	13
7.1.3	Setting of the angle of inclination	13
7.1.4	Speed of rotation	13
7.1.5	Temperature	13
7.2	Compaction	13
7.2.1	Start of compaction	13
7.2.2	Specimens for void content requirement	13
7.2.3	Specimens for further testing	14
8	Precision	14
9	Test report	15
Annex A(normative) Procedure for setting the stress for types of gyratory compactor for compactability test		16
A.1	General	16
A.2	Principle	16
A.3	Gyratory-type testing procedure	16
A.3.1	Force adjustment	16
A.3.2	Angle	16

Annex B(normative) Procedure to evaluate the gyratory compactor (GC) internal angle of gyration and related parameters using simulated loading	17
B.1 General	17
B.2 Principle	17
B.3 Procedure	17
B.3.1 Calibration procedure with internal load simulator device	17
B.3.2 Calibration procedure with dynamic angle validator device	17
B.4 Calculation of results	18
B.4.1 Calculation of results for calibration procedure with internal load simulator device	18
B.4.2 Calculation of results for calibration procedure with dynamic angle validator device	19
B.5 Compliance	20
B.6 Precision and bias	20
B.7 Report	21
Bibliography	23