ISO 19916-1:2018 (E)

Glass in building — Vacuum insulating glass — Part 1: Basic specification of products and evaluation methods for thermal and sound insulating performance

Contents

Foreword

Introduction

- 1 Scope
- 2 Normative references
- 3 Terms and definitions
- 4 Description of components
 - 4.1 Glass types and characteristics
 - 4.2 Pillars
 - 4.3 Edge seal
 - 4.4 Evacuation port
 - 4.5 Getter
- 5 Optical and thermal properties
 - 5.1 Optical properties
 - 5.2 U-value (thermal transmittance)
 - 5.2.1 Determination of the U-value
 - 5.2.2 Test report
 - 5.2.3 Calculation method for U-value of vacuum insulating glass with different glass thickness
 - 5.3 Total solar energy transmittance (g-value)
 - Dimensional requirements

6.1 Thickness

- 6.1.1 Nominal thickness
- 6.1.2 Limit deviation on thickness
- 6.1.3 Measurement of thickness
- 6.2 Width B and length H
- 6.2.1 General
- 6.2.2 Limit deviations on width B and length H
- 6.2.3 Limit deviations on squareness
- 6.2.4 Displacement

7 Durability

6

- 7.1 Requirements
- 7.2 Test specimens
- 7.3 Test method
- 8 Measurement of sound insulation
- Annex A (normative) Determination of steady-state U-value (thermal transmittance) Heat flow meter method and guarded hot plate method
 - A.1 General
 - A.2 Basic formula
 - A.3 Test apparatus
 - A.3.1 Buffer plates
 - A.3.2 Heat flow meter method
 - A.3.3 Guarded hot plate method

- A.4 Dimensions of specimen and metering area
- A.4.1 Distance from edge seal
- A.4.2 Dimensions of metering area
- A.5 Measurements

Annex B (normative) Test method for durability

- B.1 Durability test
- B.1.1 General
- B.1.2 Moisture and light resistance test
- B.1.3 Thermal repeating test
- Annex C (informative) Calculation method for thermal transmittance (U-value)
- Annex D (informative) Contribution from the edges to the measurement of the thermal transmittance (Uvalue) of vacuum insulating glass
- Annex E (informative) Maximum deviation in the measured thermal transmittance (U-value) of a vacuum insulating glass due to non-uniformities in the heat flow through the pillar array

Page count: 33