

ISO/TS 18178:2018 (E)

Glass in building — Laminated solar photovoltaic glass for use in buildings

Contents

	Foreword
1	Scope
2	Normative references
3	Terms and definitions
4	Description of components
4.1	General
4.2	Types of glass
4.3	Typical types of solar cells
4.4	Interlayer
4.5	Interconnector
4.6	Insulating strip
4.7	Termination
5	Requirements
5.1	General
5.2	Appearance
5.2.1	Major visual defects
5.2.2	Defects in the main area
5.2.3	Defects in the edge area
5.3	Dimensions and edge finishing
5.4	High temperature test
5.5	Damp heat test
5.6	Radiation test
5.7	Thermal cycling test
5.8	Humidity freeze test
5.9	Measurement of NMOT
5.10	Hot-spot endurance test
5.11	Impact test
5.12	Ball drop test
5.13	Insulation test
5.14	Wet leakage current test
5.15	Robustness of terminations test
6	Test specimens
7	Test methods
7.1	Test sequences
7.2	Visual inspection
7.3	High temperature test
7.4	Damp heat test
7.5	Radiation test
7.6	Thermal cycling test
7.7	Humidity-freeze test
7.8	Measurement of NMOT
7.9	Hot-spot endurance test
7.10	Ball drop test
7.10.1	Purpose
7.10.2	Specimen
7.10.3	Apparatus
7.10.3.1	Impactor.
7.10.3.2	Impactor hold-release device.

- 7.10.3.3 Specimen holder.
- 7.10.4 Procedure
- 7.11 Insulation test
- 7.12 Wet leakage current test
- 7.13 Robustness of terminations test

8 Designation

Page count: 13